

MW-7

1 LOCATION OF WATER WELL: County: Doniphan Fraction: SW 1/4 SW 1/4 NE 1/4 Section Number: 36 Township Number: T 03 S Range Number: R 22 EW

Distance and direction from nearest town or city street address of well if located within city? 2009 Roseport Road, Elwood

2 WATER WELL OWNER: Tektron, Inc. RR#, St. Address, Box #: 100 Virginia Center Parkway City, State, ZIP Code: Providence, RI 02903 Board of Agriculture, Division of Water Resources Application Number: -

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Diagram showing a 3x3 grid with 'X' in the center] 4 DEPTH OF COMPLETED WELL: 21.67 ft. ELEVATION: 813.44 ft. WELL'S STATIC WATER LEVEL: 16.13 ft. below land surface measured on 01/27/05

5 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 2 in. to 11.5 ft., Dia. Casing height above land surface: -0.53 in., weight. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 21.5 ft. to 11.5 ft. GRAVEL PACK INTERVALS: From 23 ft. to 10.5 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 10.5 ft. to 2 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? N-NE How many feet? 105

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0 to 1.0 (Asphalt), 1.0 to 2.0 (silty clay (CL)), 2.0 to 23 (silt/very fine sand (ML))

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01/26/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 650 This Water Well Record was completed on (mo/day/yr) 03/04/05 under the business name of Deffenbaugh Field Services by (signature) [Signature]