											•		
			WATE	R WELL RECORD	Form WWC	-5 KSA 82a	-1212						
1 LOCATI	ON OF WA	TER WELL:	Fraction		Se	ction Number	Township No	ımber	R	ange N	lumber		
County:	Washing	ton	NW ¼	NW ¼	SE ¼	2	T 3	S	R	3	Œ	W	
		n from nearest tow Str., Washingto	•	address of well if loo	cated within city	/?							
ì	_												
		WNER: Twin Sta		LC									
		×# : P.O. Box					Board of Agricu		sion of \	Nater I	Resour	ces	
-	, ZIP Code	,	Nebraska 6				Application Nur						
3 LOCATI	E WELL'S	LOCATION Z ECTION BOX:	DEPTH OF C	OMPLETED WELL.	28	ft ELEV	аті <b>он</b> :	1	333.87				
VVIIIIA		N .  [		twater Encountered									
T r		<u>'</u>  v	VELL'S STATIC	WATER LEVEL	.19.13 ft	below land su	rface measured o	n mo/day/	yr	2/5	/98		
T L			Pump test data: Well water wasNAft. after hours pumping gpm Est. Yield NAgpm: Well water wasft. after hours pumping										
	NW	NE E											
<u>.</u>				eter 8 in.									
W W		<u>└</u> Fi,		TO BE USED AS:			8 Air conditioning		Injection				
-			1 Domestic				9 Dewatering	•	•				
	SW	SE							•	•		•	
		1 1 1	2 Irrigation				Monitoring well						
♦				l/bacteriological san	npie submitted				, mo/day			<i>r</i> as	
		3	submitted		_		ter Well Disinfecte			No	•		
5 TYPE C	OF BLANK	CASING USED:		5 Wrought iron	8 Conc	rete tile	CASING JOI	NTS: Glue	d	. Clan	nped		
1 St	teel	3 RMP (SR)		6 Asbestos-Cemer	nt 9 Othe	(specify below	w)	Wek	ded				
(2)P\	VC	4 ABS		7 Fiberglass				Thre	aded. ؠ	<b>/</b>			
Blank casir	ng diamete	r <b>.2</b>	in. to 1	8 ft., Dia	in.	to	ft., Dia		. in. to			ft	
	•			in., weight									
_	•	R PERFORATION		, 3	(7)P\			estos-cem					
=						RMP (SR) 11 Other (specify)							
2 Br		•	d steel	6 Concrete tile 9 ABS 12 None used (open hole)									
		RATION OPENING			uzed wrapped	_					on hak	٥)	
	ontinuous s				• •		9 Drilled holes		II INC	nie (ot	en nor	<del>e</del> )	
_	ouvered shu		y punched		ch cut								
SCREEN-F	PERFORAT	ED INTERVALS:		. 18 ft. to		•							
_													
G	BRAVEL PA	CK INTERVALS:		. 16 ft. to									
			From	fL to	· · · · · · <u>· ·</u> · · · ·	ft, Fro	om	ft.	to			f	
6 GROUT	MATERIA	L: 1 Neatce	ement	2 Cement grout	3 Bent	onite 4	Other						
Grout Inter	rvals: Fro	m	ft to 1 🕏	ft., From	14 ft								
		ource of possible of					tock pens		bandon				
		4 Latera		7 Pit privy									
•				8 Sewage k	2000p	11 Fuel storage 15 Oil well/Gas well on 12 Fertilizer storage (16) Other (specify below							
				-	-		cticide storage						
Direction f	ertight sew		ide hir	9 Feedyard			ny feet? 295	· · · · A	ST Ta	IIKS ·		• • •	
		West	LITHOLOGIC	TOG	LDCWA			UGGINGT	KITIEDA //	u e			
FROM	10	Class Day 1 D			FROM	10	PL	CASISON I	HICKVA				
0	3	Clay, Dark Br	UWN			+ +							
3	10	Clay, Brown											
10	17	Clay, Red Bro				<u> </u>							
17	28	Clay, Orange-	Brown										
									<del></del> _				
						1							
	<del> </del>												

MW8, Tag # 00263030, Flushmount Project Name: Farmers Oil Company GeoCore # 556, KDHE # A5 101 40126 

by (signature)

. .2/1.0/98. . . . . . .

×

GeoCore Services, Inc.

under the business name of