

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:		County <b>Washington</b>	Fraction <b>N. 1/4 4</b> <b>NW 1/4 NW 1/4 NW 1/4</b>	Section number <b>25</b>	Township number <b>T 3 South</b>	Range number <b>R 5 east</b>
2. Distance and direction from nearest town or city: Street address of well location if in city:		<b>4 MI north</b> <b>of Barnes on east</b>		3. Owner of well: R.R. or street: <b>Leo J neck</b> <b>Barnes Kans</b>		
4. Locate with "X" in section below: N W E S 1 Mile		Sketch map: <b>Side of road</b>		6. Bore hole dia. <b>12</b> in. Completion date <b>11-16-76</b> Well depth <b>60</b> ft.		
5. Type and color of material		From		To		7. <input checked="" type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary
		8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input checked="" type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other				
Topsoil		0		4		9. Casing Material <b>STEEL</b> Height: Above or below Threaded <input checked="" type="checkbox"/> Welded <input type="checkbox"/> Surface <b>13</b> in. RMP <input checked="" type="checkbox"/> PVC <input type="checkbox"/> Weight <b>24</b> lbs./ft. Dia. <b>1 1/2</b> in. to <b>36</b> ft. depth <input checked="" type="checkbox"/> Well Thickness inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth <input checked="" type="checkbox"/> No. <b>231</b>
Clay Joint & Brown		4		30		10. Screen: Manufacturer's name <b>Pumpco</b> Type <b>MSP10</b> Dia. <b>5</b> Slot/gauze <b>0.40</b> Length <b>20'</b> Set between <b>30</b> ft. and <b>30</b> ft. ft. and <input type="checkbox"/> ft.
Sandy		30		34		Gravel pack? <input checked="" type="checkbox"/> Size range of material <b>2-4</b>
gravel; Flint		34		36		11. Static water level: <b>30</b> ft. below land surface Date <b>11-16-76</b>
Chalk Blue		36		38		12. Pumping level below land surfaces: ft. after _____ hrs. pumping _____ g.p.m. ft. after _____ hrs. pumping _____ g.p.m. Estimated maximum yield <b>30</b> g.p.m.
Rock, Limestone		38		50		13. Water sample submitted: _____ mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date _____
Shale Blue		50		60		14. Well head completion: <input type="checkbox"/> Pitless adapter _____ Inches above grade <input checked="" type="checkbox"/> Well grouted? <input checked="" type="checkbox"/> <b>1-2</b> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From <b>16</b> ft. to <b>5</b> ft.
(Use a second sheet if needed)						16. Nearest source of possible contamination: ft. <b>65</b> Direction <b>NORTH</b> Type <b>Barn</b> Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
						17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name _____ Model number _____ HP _____ Volts _____ Length of drop pipe _____ ft. capacity _____ g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other
18. Elevation: <b>510'</b>	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>Strader Drilling Co 23</b> Business name <b>Blue Rapids</b> License No. _____ Address _____ Signed <b>Harold Strader</b> Date <b>11-16-76</b> Authorized representative			

T-3  
 R-5  
 W-25  
 Sec  
 NW 1/4  
 NW 1/4