3		RECORD	Form WWC-	5	Division	of Water F	Resources; App. No.			
1 LOCA	TION OI	WATER WELL:	Fraction	S	Section N	umber	Township Number	Range Number		
Count	y: Marsh	all	CS 1/4 SE 1/4 \$				T 3 S	R 7 (E) W		
Distance and direction from nearest town or city street address of well if located within city? Approximately 2 3/4 miles east and 4 miles south of						Global Positioning Systems (decimal degrees, min. of 4 digits)				
Marysville						Latitude: 39.78371				
2 WATER WELL OWNER: City of Marysville						Longitude: -96.584305 Elevation: Unknown				
RR# St Address Roy # . City Hall						Datum: NAD83				
City, State, ZIP Code 209 N. 8th St. : Marysville, KS 66508						Data Collection Method: WAAS GPS Unit				
21004										
T 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1										
WITH AN "X" IN SECTION BOX:  Depth(s) Groundwater Encountered (1) ft. (2) ft. (3)  WELL'S STATIC WATER LEVEL 47.05 ft. below land surface measured on mo/day/yr 07-15-08										
SECTION BOX: WELL'S STATIC WATER LEVEL 47.05 ft. below land surface measured on mo/day/yr 07-15-08										
Pump test data: Well water was Not checked ft. after hours pumping g  Est. Yield Unknown gpm: Well water was ft. after hours pumping g										
WELL WATER TO BE LICED AC. 5 P.11.										
W   E   1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify below)    SW   SE   2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Test Well										
-sw	SE									
	1,	Was a chemical/bacte								
Sample was submitted Water well disinfected? Yes No										
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped										
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded										
2 PVC 4 ABS 7 Fiberglass Threaded										
2 PVC 4 ABS 7 Fiberglass Threaded  Blank casing diameter 5 in. to 98 ft., Diameter in. to ft., Diameter in. to ft.  Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No214										
Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL:  13										
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1 Continuous det (2) Millelet 5 Coursed arround 7 Torch out 0 Deilled below 11 News (even below										
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify)										
SCREEN-PERFORATED INTERVALS: From 98 ft. to 138 ft., From ft. to ft.										
From ft. to ft., From ft. to								ft.		
GRAVEL PACK INTERVALS: From 34 tt. to 81 ft., From tt. to							ft.			
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (Specify)  SCREEN-PERFORATED INTERVALS: From 98 ft. to 138 ft., From ft. to ft.  From ft. to ft., From ft. to ft.  GRAVEL PACK INTERVALS: From 34 ft. to 81 ft., From ft. to ft.  From 81 ft. to 139 ft., From ft. to ft.										
Theat center 2 center grow (3) periodite 4 Other										
Grout Intervals: From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:  What is the nearest source of possible contamination:  10 Liverteek person 12 Inserticide Storage (16) Other (specific										
1 Septic tank 4 Lateral lines / Pit privy 10 Livestock pens 13 insecticide Storage 100 Other (spec							Other (specify			
2 Sewer	rlines	•	Sewage lagoon 1				4 Abandoned water well below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well None known										
		?		low many	T		PLANCE DE DES			
FROM	TO	LITHOLOGIC LO	)G	FROM	TO		PLUGGING INT	ERVALS		
0 4	9	Topsoil Clay, light gray, hard		94	103	sand, s	ιnd gravel, coarse	to fine with clay		
9	15	Clay, light gray, hard		94	103		s, light gray	to line, with clay		
15	44	Clay, light gray, hard		103	137.5		coarse to fine			
44 .	53	Sand and gravel, very fin	e to coarse, with	137.5	140		ne, dark gray color, ver	y hard, pull down		
		rock streaks, large, and cement	· · · · · · · · · · · · · · · · · · ·				<u> </u>	.,		
53	86	Sand and gravel, fine to								
		streaks, large, and cemer								
86	89	Clay, brown and tan, hard		ļ						
89	90	Cemented sand, hard, pu								
90 94 Clay, gray, hard, with streaks, cemented 7 CONTRACTOR'S OR I ANDOWNER'S CERTIFICATION. This water will use (1) (2) recent and (2) released										
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed (3) plugged under my jurisdiction and was completed on (mo/day/year) 07-15-08 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/year) 07-21-08										
i		ame of Clarke Well & Equip			gnature)	15	~~			
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three										
copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.										
1	50:10 01	TILLE TILL O TILLE AND I	One for four records.	- 20 OI WJ.00	-01 Jucii <u>00</u>			•		