


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Marshall	Fraction NE 1/4 NE 1/4 NW 1/4	Section number 32	Township number T 3 S R 9 E/X
2. Distance and direction from nearest town or city: Frankfort; 3/4 Mi. W. Street address of well location if in city:			3. Owner of well: R.R. or street: Marshall County RWD #3 City, state, zip code: Frankfort, Kansas		
4. Locate with "X" in section below:  Sketch map: Well No. 1		6. Bore hole dia. 30 in. Completion date 1/30/80 Well depth 93 1/2 ft.			
5. Type and color of material		From	To	7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
Fill dirt		0	3	8. Use: <input type="checkbox"/> Domestic <input checked="" type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Soil		3	6	9. Casing: Material Stl. Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 24 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 34.24 lbs./ft. Dia. 10 in. to 8 1/2 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 330	
Clay		6	35	10. Screen: Manufacturer's name Johnson Wire Wrap (Stainless) Type Wire Wrap Dia. 16" Slot/gauze #40 Length 10' Set between 8 1/2 ft. and 9 1/2 ft. Gravel pack? yes Size range of material .012-.09	
Med. to coarse sand & gravel w/boulders		35	42	11. Static water level: 5 ft. below land surface Date 5/24/79	
Fine sand		42	85	12. Pumping level below land surfaces: 67 ft. after 5 hrs. pumping 266 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 275 g.p.m.	
Med. to coarse sand & gravel w/boulders		85	93	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/>	
Blue shale		93		14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 36 Inches above grade	
				15. Well grouted? Yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 7 ft. to 27 ft.	
				16. Nearest source of possible contamination: ft. 1500 Direction NW Type Farm Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
				17. Pump: Manufacturer's name Layne & Bowler Model number 6RKHC HP 15 Volts 460 Length of drop pipe 84 ft. capacity 260 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name License No. Address Wichita, Kansas Signed Donald Aguirre Date 1/3/80 Authorized representative	