			WATE	R WELL RECORD	Form WWC	5 KSA 82a-121	12 ID No	MW-7	
1 LOCATI	ON OF WATE	R WELL:	Fraction		:	Section Number	Township Nur	mber I	Range Number
County:	Br	own	NW 1/4		SW 1/4	33	т 4	S F	17 (B)W
			town or city street add	ress of well if loca	ated within city	?			
	venue East			·	TWP				
			ies Oil Company						
			nway 36, P.O. Box	338			Board of Agricu	lture, Division o	f Water Resources
City, State,	ZIP Code	: Troy	, Kansas 66087				Application Nur	nber:	
3 LOCATE AN "X" II	E WELL'S LOC N SECTION B	CATON W BOX:	1TH 4 DEPTH OF C	OMPLETED WEL	L	30.0 ft. ELEVA	TION:		
	N		Depth(s) Ground	water Encountered	1	<b>19.0</b> ft.	2	ft. 3	ft.
I <b>≜</b> Γ			WELL'S STATIC	WATER LEVEL	13.01	ft. below land su	face measured or	n mo/day/yr	08/05/04
	NW	. NE							ng gpm
	1400	IAE							ng gpm
§ w L		l	E Bore Hole Diame	ter 85 in	to.	30.0 6	t and	in to	ft
- X			WELL WATER TO	O BE USED AS:	5 Public wat	er supply	8 Air condition	ina 11 Inie	ction well er (Specify below)
• · ·		SE	1 Domestic	3 Feed lot	6 Oil field wa	iter supply	9 Dewatering	12 Oth	er (Specify below)
	!	!	2 Irrigation	4 Industrial	7 Lawn and	garden (domestic)	(0)Monitoring	well	ay/yr sample was
♦ L			Was a chemical/b	acteriological san	nple submitted	to Department? Y	esNo	If yes, mo/d	ay/yr sample was
	S		submitted				r Well Disinfected		
5 TYPE O	F BLANK CAS	SING USF		5 Wrought Iron	8 Cc				Clamped
1 Ste			MP (SR)	-		her (specify below			
(2) PV		4 AE	` '				•		X
				7 Fiberglass		·	4 Di-		
Blank casin	ng diameter	2.3/3	in. to 10.0	tt., Dia		in. to	π., Dia	in. to	Cohodul- 40
Casing heig	ght above land	surface	Flush Mount TION MATERIAL:	in., weight		lbs./ft. V	Vall thickness or g	auge No.	ocnedule 40
		PERFORA	TION MATERIAL:		(	7) PVC	10 Asbes	stos-cement	
1 Ste		3 St	ainless steel	5 Fiberglass		8 RMP (SR)	11 Other	(specity)	
2 Bra			alvanized steel	6 Concrete tile		9 ABS	12 None	used (open hol	e)
SCREEN	JR PERFORA	TION OPE	NINGS ARE:	5 (	Jauzed wrapp	ea		11 1	vone (open noie)
2 10	ontinuous siot	. (	3 Mill slot Key punched	0 \ 7 -	Vire wrapped Forch cut		9 Drilled holes 10 Other (specif	ω\	
			4 Key punched	20.0		0 0 =	To Other (specif	у)	
SCREEN-P	PERFORATED	INTERVA							ft.
									ft.
GR	RAVEL PACK I	NTERVAL	S: From						ft.
			From	ft. to		ft. Fro	om	ft. to	ft.
6 GROUT	MATERIAL:	1 N	eat cement 🕹	Cement grout	હ	Bentonite 4	Other		
Grout Interv	vals From	0.0	ft. to 2.0	ft. From	2.0	ft. to 7.0	ft. From	ft.	toft.
			ble contamination:			10 Livesto		14 Abandon	
1 Se	ptic tank		4 Lateral lines	7 Pit	privy	(11) Fuel sto	orage	15 Oil well/	Gas well
2 Se	wer lines		5 Cess pool	8 Sev	wage lagoon	12 Fertilize	er storage	16 Other (sp	ecify below)
3 Wa	atertight sewer	rlines	6 Seepage pit	9 Fee	edyard	13 Insection	ide storage		
Direction fro				est		How many fe	eet?	190	
FROM	TO	CODE			L	ITHOLOGIC LOG			
0.0	0.5		Asphalt						
0.5	18.0		Brown-red brown	very silty cla	y, laminate	d, very firm, m	oist, trace odo	or	
18.0	28.5		Tan-olive very sil						
28.5	30.0		Olive-gray very s	ilty clay, very	firm, moist	trace odor	W-150-00		
			,						
									*
	Flush-mount well completion approved by Don Taylor, KDHE, BOW.								
7 CONTR	ACTOR'S OR	LANDOW	NER'S CERTIFICATION	ON: This water we	ell was (1) cons	tructed, (2) reconst	tructed, or (3) plug	ged under my ju	risdiction and was
completed on (mo/day/yr) 07/23/04 and this record is true to the best of my knowledge and belief. Kansas									
Water Well	Contractor's L		).	692	Th	is Water Well Rec	ord was complete	Mondayiy	06/06/04
ı	usiness name			State Service			(signature)	THULL "	W/
INSTR	RUCTIONS: PI	ease fill in b	planks and circle the corre	ect answers. Send t	hree copies to h	Cansas Department	of Health and Enviro	onment, Bureau o	Water, 1000 S W
Jackso	on St., Ste. 420,	Topeka, K	ansas 66612-1367. Tele	phone: 913-296-55	45. Send one t	WATER WELL OV	VNER and retain on	e fér your record	¥