		LL RECORD	Form W	WC-5	Division of Water Resources App. No.	
1 LOCATION OF WATER WELL: County: Brown		Fraction SW 1/4 SW 1/4 SE		Section Number Township No. Range Number		
Stre	Street/Rural Address of Well Location; if unknown, distance & direction				Global Positioning System (GPS) information:	
fron	from nearest town or intersection: If at owner's address, check here [].				Latitude: .39. 40.925 (in decimal degrees)	
		and 120 Rd		Section 18	Longitude: 95 27.403 (in decimal degrees) Elevation: 1100	
2 337.4	PRINTING WW.	EST & OFFICE AS			— <u>Datum</u> : ☑ WGS 84, □ NAD 83, □ NAD 27	
			States Geological S	urvey	Collection Method:	
RR#, Street Address, Box #: 4821 Quail Crest Place City, State, ZIP Code : Laurence KS 6240				GPS unit (Make/Model: Garmin St Pilot 3		
City	, State, 2	Lawren	ce, KS 66049		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey	
3 100	CATE WE	YY			Est. Accuracy:	
	H AN "X		COMBRIDE INTERNATION	× 28.6	ft.	
	TION BO	Donth(a) Ground	COMMENSIED WES	40 49:9		
220	N	~ op m/o/ Cround	CWATER TEXTS	(1)9	ft. (2)	
l		Pump	tost detay Well was		ft. below land surface measured on mo/day/yr10/3/10	
	<u>' </u>	FST VIELD	ann Wall wat	er was	ft. after hours pumping gpm	
w N	W N	E Bore Hole Diam	otor 8 1/4" in to	28 6	ft. after	
W		WELL WATER	TO DE HEED AC. I		.ft., andft.	
'	'		TO BE USED AS: [Public wa	rater supply Geothermal Injection well	
S	swse Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well						
	S					
S If yes, mo/day/yr sample was submitted						
		ASING USED: Stee		Other	***************************************	
CASIN	IG JOIN	ΓS: ☐ Glued ☐ Clar	nped Welded	Thread	led	
Casing diameter .2.1/2" in. to .28.6						
Casing height above land surface. 30 in. Weight lbs/ft. Wall thickness or gauge No. Schedule 80						
LYPE	OF SCR	EEN OR PERFORATION	MATERIAL:			
Steel Stainless Steel PVC Other (Specify)						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From 28.6 ft. to 18.6 ft., From ft. to ft.						
From						
Trong A. J.						
From						
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other						
What is the nearest source of possible contamination:						
Septic tank						
Sewer lines						
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well						
Dire	ction fron	n well	***********		e from well	
FROM	TO	LITHOLOG		FROM	TO LITHO. LOG (cont.) or PLUGGING INTERVALS	
0	14	Brown Clay				
14	19	Sandy Yellow Clay				
19	20	Gravel				
20	28.6	Silt, Sands and Gravel		1		
				 		
	1					
	1			1		
				 		
				 		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 🗸 constructed, 🗌 reconstructed, or 🗌 plugged						
under my jurisdiction and was completed on (mo/day/year) .10/3/10 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 823 This Water Well Record was completed on (mo/day/year) 10/13/10						
under the business name of United States Geological Survey by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in branks and check the correct answers. Send three copies						
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at						
		ov/waterwell/index.html.		. James Ville IVI	, and and any of the same additional work. Visit us a	
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy						