The large Number of the la	1
	ber E
Distance and direction from nearest town or city street address of well if located within city? 1505 Central, Horton KS Clobal Positioning System (decimal degrees, min. of 4 of Latitude: NA Longitude: NA NA NA	igits)
2 WATER WELL OWNER: KDHE Elevation: NA	
RR#, St. Address, Box # : 1000 SW Jackson Datum: NA	
City, State, ZIP Code : Topeka, KS 66612 Data Collection Method: legal survey 3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 19.5 ft.	
LOCATON MW5	
	ft.
SECTION BOX: WELL'S STATIC WATER LEVEL 4.30 ft. below land surface measured on mo/day/yr 10/24	/11 gpm
N Pump test data: Well water was ft. after hours pumping Est. Yield gpm: Well water was ft. after hours pumping	gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well	
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify by	low)
W	
-swse	,
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/da Sample was submitted Water Well Disinfected? Yes No TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clampe	yrs X
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clampe	1
1 Steel 3 RMP (SR) 6 Ashestos-Cement 9 Other (specify below) Welded	
PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2 in. to 5 ft., Dia in. to ft., Dia in. to Casing height below land surface NA ft., Weight lbs./ft. Wall thickness or gauge No.	
Blank casing diameter 2 in. to 5 tt., Dia in. to T., Dia in. to The Well thickness or gauge No	· 11.
Casing height below land surface NA ft., Weight ibs./it. Wall unckness of gauge No.	
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 9 ABS 11 Other (specify)	j
2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 5 ft. to 19.5 ft. From ft. to	ft.
From It. to II. From It. to	IL.]
GRAVELPACK INTERVALS: From 3 ft. to 20 ft. From tt. to	nt.
From tt. to tt. From tt. to	11.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Concrete: 0-1ft Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. to	
Grout Intervals From 1 ft. to 3 ft. From ft. to ft. From ft. to	ft.
What is the nearest source of possible confiamination:	1
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (s	ecny
2 Sewer lines 5 Cess pool 8 Sewage lagoon (1) Fuel storage 14 Abandoned water well below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well	
Direction from well? E How many feet? ~100ft	
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVA	LS
0 1 Topsoil	
1 8 Stiff to hard, dark brown-gray brown, silty clay	
8 12 Stiff to hard, gray brown, silty clay w/ Fe staining	
12 20 Stiff to hard, brown-gray brown, silty clay w/ Fe staining, trace fine	
sand, gravel	
Flushmount waiver from BOV	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, S) econstructed, or (3) p under my jurisdiction and was completed on (mo/day/year) Kansas Water Well Contractor's License No. 757 This Water Well Record was completed in (mo/day/year) 11/4/11	ugged belief.
under the business name of Larsen & Associates, Inc. by (signature) New York Control of Warren Contro	ter ·
INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of W. Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send on the WATER WELL OWNER and retain	one for