

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BROWN		SW 1/4 NW 1/4 SW 1/4	28	T 4 S	R 17 E/W
Distance and direction from nearest town or city street address of well if located within city? 1712 CENTRAL - HORTON					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : 1712 CENTRAL PO BOX 23		Application Number:			
City, State, ZIP Code : HORTON KS 66439					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION: 23 ft.			
		Depth(s) Groundwater Encountered 1. 21 ft. 2. 23 ft. 3. - ft.			
		WELL'S STATIC WATER LEVEL 23.21 ft. below land surface measured on mo/day/yr 11-10-94			
		Pump test data: Well water was - ft. after - hours pumping - gpm			
		Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm			
		Bore Hole Diameter: 8.375 in. to 27 ft. and - in. to - ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 <u>Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes - No X ; If yes, mo/day/yr sample was submitted -			
		Water Well Disinfected? Yes - No X			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued - Clamped -
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded -
			7 Fiberglass		Threaded X
Blank casing diameter 2 in. to 17 ft. Dia - in. to - ft. Dia - in. to - ft.					
Casing height above land surface 24 in. weight SCH 40 lbs./ft. Wall thickness or gauge No. -					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) -
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 <u>Mill slot</u>	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify) -	
SCREEN-PERFORATED INTERVALS: From 17 ft. to 27 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft.					
GRAVEL PACK INTERVALS: From 16 ft. to 27 ft. From - ft. to - ft. From - ft. to - ft. From - ft. to - ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 <u>Cement grout</u>	3 <u>Bentonite</u>	4 Other -	
Grout Intervals: From 0 ft. to 14 ft. From 14 ft. to 16 ft. From - ft. to - ft. From - ft. to - ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	VERY CONTAMINATED SITE
Direction from well? -		How many feet? -			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	-SOIL-CLAY SILT			
2	9	SILTY CLAY			
9	14	SILTY CLAY BR/GRAY			
14	22	SANDY CLAY			
22	27	SILTY SAND-ORANGE			
TD	27				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-09-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 11-14-94					
under the business name of EBBERTS DRILLING by (signature) <i>[Signature]</i>					