Digital Record Correction Change in Well Use Resources App. No. Well ID	MW8
County: BTOWN	1
WELL OWNER: Last Name Business USDA Address	
Busines	
Address:	ce and
Address	here:
ASHINGTON DC State ZIP 20250	ST
A DEPTH OF COMPLETED WELL:	
WITH "X" IN SECTION BOX: N Comparison of the content of the co	
SECTION BOX: Depth(s) (roundwater Encountered: 1)	
WELL'S STATIC WATER LEVEL:	
below land surface, measured on (mo-day-yr). GPS (unit make/model: _!PHONE_ (WAAS enabled? Yes No) Land survey Topographic Map Charles Nous pumping gpm Gestimated Yield: Survey Topographic Map Charles	NAU 21
www. well and surface, measured on (no-day-yr) (WAS canabled? yes no) no no no no no no n	,
Pump test data: Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm Stimated Yield: gpm Bore Hole Diameter: ft. in. to ft. ft. december ft.	
Well water was fi. after hours pumping gpm well water was fi. after hours pumping gpm Bore Hole Diameter: fi. fi. Ground Leve Source: Land Survey GPS Topogra GPS Topo	
Well water was	
Estimated Yield:	
Source: Land Survey GPS Topogra Continuous Source: Land Survey GPS Topogra Source: Source: Land Survey GPS Topogra Source: Land Survey GPS Topogra Source: Source: Land Survey Gestechnical Land Survey Gestech	1 П тос
TWELL WATER TO BE USED AS: Dublic Water Supply: well ID	
1. Domestic:	
Household	
Lawn & Garden	
Livestock 8. Monitoring: well ID MW8 12. Geothermal: how many bores? 2. Irrigation 9. Environmental Remediation: well ID a) Closed Loop Horizontal Vertical 4. Industrial Recovery Injection 13. Other (specify): No If yes, date sample was submitted: Water well disinfected? Yes No No No No No No No N	
Casing diameter Steel Stainless Steel Fiberglass PVC Steel Stainless Steel Fiberglass Contribuous Slot Mill Slot Gauze Wrapped Sone Contribuous Slot Mill Slot Gauze Wrapped ScreEn-PERFORATION OPENINGS ARE: Contribuous Slot Mill Slot Gauze Wrapped ScreEn-PERFORATED INTERVALS: From 20. ft. to 25. ft., From ft. to ft., From ft., Fr	
3. Feedlot	
Was a chemical/bacteriological sample submitted to KDHE?	
Water well disinfected?	
Water well disinfected?	
S TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Tasing diameter 2 in to 20 ft., Diameter in to ft., Diameter in to ft. Casing height above land surface 30 in Weight Ibs./ft. Wall thickness or gauge No. SCH 40	
Casing diameter 2 in. to 20 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 30 in. Weight lbs./ft. Wall thickness or gauge No. SCH 40. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 20 ft. to 25 ft., From ft. to ft., From ft. to GRAVEL PACK INTERVALS: From 15 ft. to 28. ft., From ft. to ft., From ft. to GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Seever Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Direction from well? Distance from well? Distance from well? FROM TO LITHOLOGIC LOG FROM TO LITHOLOG (cont.) or PLUGGING INTO 13 CLAY-SILTY, SANDY	Threaded
Casing height above land surface	
Steel Stainless Steel Fiberglass Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From .20 ft. to .25 ft., From ft. to ft., From ft. ft. ft. ft. ft. ft. ft. ft. ft.	
□ Brass □ Galvanized Steel □ Concrete tile □ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: □ Continuous Slot ■ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify) □ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From .20	
SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Saw Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 20 ft. to 25 ft., From ft. to ft., From ft. to GRAVEL PACK INTERVALS: From 15 ft. to 28 ft., From ft. to ft., From ft., From ft. to ft., From ft., F	
□ Continuous Slot ■ Mill Slot □ Gauze Wrapped □ Torch Cut □ Drilled Holes □ Other (Specify) □ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole) SCREEN-PERFORATED INTERVALS: From 20	
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From . 20	
SCREEN-PERFORATED INTERVALS: From 20	
GRAVEL PACK INTERVALS: From 15 ft. to 28 ft., From ft. to ft., From ft. to	A
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 2 ft. to 15 ft., From ft. to ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? Distance from well? 10 FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTO 13 CLAY-SILTY 14 CLAY-SILTY, SANDY	
Nearest source of possible contamination: Septic Tank	11.
Nearest source of possible contamination: Septic Tank	
Septic Tank	
Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? Distance from well? Ithough To LITHOLOGIC LOG FROM TO LITHOLOGION OF PLUGGING INTO 13 CLAY-SILTY 14 CLAY-SILTY, SANDY	
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well ☐ Other (Specify) ☐ Distance from well? ☐ Distance from well? ☐ ft. 10 FROM TO LITHOLOGIC LOG FROM TO LITHOL LOG (cont.) or PLUGGING INTO 0 13 CLAY-SILTY ☐ CLAY-SILTY ☐ CLAY-SILTY 13 14 CLAY-SILTY, SANDY ☐ CLAY-SILTY	
Direction from well? Distance from well? ft.	
10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INT 0 13 CLAY-SILTY 13 14 CLAY-SILTY, SANDY	
0 13 CLAY-SILTY 13 14 CLAY-SILTY, SANDY	
13 14 CLAY-SILTY, SANDY	TERVALS
14 23 SAND	
23 28 CLAY-SILTY, SANDY	
Notes:	
	10:
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or	J plugged
under my jurisdiction and was completed on (mo-day-year) .4-12-2023 and this record is true to the best of my knowledge an	2 ?
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo-day-year)	
Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section	n,
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.	
Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10	0/2015