KOLAR Document ID: 1454414

WATER				WWC-5			vision of Wate					
Original		Correction		ge in Well Use			ources App. N			Well ID		
1 LOCATION OF WATER WELL: Fraction							ction Numbe	er	Township Numb		nge Number	
County: 1/4 1/4 1/4 2 WELL OWNER: Last Name: First: S						1⁄4	1 4 1 1					
2 WELL C Business:	ist Name:	First:		eet or Rural Address where well is located (if unknown, distance and ction from nearest town or intersection): If at owner's address, check here:								
Address:												
Address:												
City:			State:	ZIP:								
3 LOCATE WELL WITH WY N 4 DEPTH OF COMPLETED WELL:							5 Latit	nqe.			(decimal degrees)	
WITH "X" IN SECTION BOX:												
	SECTION BOX: 2) ft. 3) ft., or 4) \Box					Dry Well Datum: WGS 84 NAD 83 NAD 27						
	- V		VELL'S STATIC WATER LEVEL:				Sourc		Latitude/Longitude			
	X	below land surface, measured on (mo-day-yr)							unit make/model:			
NW	- NE	□ above land surface, measured on (mo-day-yr). Pump test data: Well water was ft.						(WAAS enabled? Yes No)				
w	Е	after hours pumping				m		□ Land Survey □ Topographic Map □ Online Mapper:				
		Well water was ft.										
SW	SE	after hours pumping gpr				m						
		Estimated Yield:gpm					6 Elevation:ft. Ground Level TOC					
S	1 1	Bore Hole I	Bore Hole Diameter: in. to f				Source: Land Survey GPS Topographic Map					
7 WELL WATER TO BE USED AS: 1. Domestic: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease 												
□ Household												
Lawn &		7. Aquifer Recharge: well ID										
	Livestock 8. Monitoring: well ID											
2. 🗌 Irrigatio	n			al Remediation: well								
3. 🗌 Feedlot 🔅 Air Sparge 🔅 Soil Vap					or Exti							
4. □ Industrial □ Recovery □ Injection 13. □ Other (specify):												
Was a chemical/bacteriological sample submitted to KDHE? \Box Yes \Box No If yes, date sample was submitted:												
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded												
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No												
TYPE OF SCREEN OR PERFORATION MATERIAL:												
$\Box \text{ Steel} \Box \text{ Stainless Steel} \Box \text{ Fiberglass} \Box \text{PVC} \Box \text{ Other (Specify)} \dots \dots$												
□ Brass □ Galvanized Steel □ Concrete tile □ None used (open hole)												
SCREEN OR PERFORATION OPENINGS ARE:												
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)												
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)												
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. to ft.												
	GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft. o ft. o ft. o ft.											
				. ft., From							•••••	
Nearest source			on: No	potential source of c	ontam	nination wi	thin 200 ft.			11.		
Septic T			Lateral Line				Livestock Pe	ens	Insection	cide Storag	e	
Sewer L			Cess Pool	Sewage			Fuel Storage		Abando			
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well												
Direction from well? ft.												
10 FROM	TO		ITHOLOG		wen?	FROM	ТО		π. ΉΟ. LOG (cont.) or		IG INTERVALS	
	10	1				11000	10		110. LOG (cont.) 01	120001		
ļ												
ļļ						N T 4						
├						Notes:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, a reconstructed, or plugged												
under my jui	risdiction an	d was compl	leted on (n	no-day-year)		and	this record	is tru	ie to the best of m	y knowled	lge and belief.	
Kansas Wate	er Well Con	tractor's Lice	ense No	This '	Water	Well Red	cord was con	mple	eted on (mo-day-ye	ear)		
under the bu	siness name	of			· · · · · · · ·	£				11		
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.												
-		ks.gov/waterwel				20000		, - °P ʻ			SA 82a-1212	