


1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 29 Township Number T 4 (S) Range Number R 3 (EW)
 County: WASHINGTON
 Distance and direction from nearest town or city street address of well if located within city? 2E-1/4 OF LINN

2 WATER WELL OWNER: Bob Okde
 RR#, St. Address, Box #: Box 73 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Linn 66953 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 100 ft. ELEVATION: 700
 Depth(s) Groundwater Encountered 1. 70 ft. 2. 70 ft. 3. 70 ft.
 WELL'S STATIC WATER LEVEL 58 ft. below land surface measured on mo/day/yr 8-3-82
 Pump test data: Well water was 58 ft. after 8 hours pumping 40 gpm
 Est. Yield 40 gpm: Well water was 100 ft. after 100 hours pumping 100 gpm
 Bore Hole Diameter 8 in. to 8 ft., and 8 in. to 8 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes L No L; If yes, mo/day/yr sample was submitted L
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued L Clamped L
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded L
 2 PVC 4 ABS 7 Fiberglass Threaded L
 Blank casing diameter 5 in. to 0-70 ft., Dia. 5 in. to 0-70 ft., Dia. 5 in. to 0-70 ft.
 Casing height above land surface 29 in., weight 2.82 lbs./ft. Wall thickness or gauge No. 2.58
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) L
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) L
 SCREEN-PERFORATED INTERVALS: From 70 ft. to 100 ft., From 70 ft. to 100 ft.
 From 70 ft. to 100 ft., From 70 ft. to 100 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 100 ft., From 10 ft. to 100 ft.
 From 10 ft. to 100 ft., From 10 ft. to 100 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other L
 Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? S How many feet? 172

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	4	Top Soil			
4	16	Clay grey			
16	22	Shale yellow			
22	45	Shale grey			
45	58	Shale yellow			
58	62	Shale red			
62	118	SANDSTONE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-3-82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 9-10-82 under the business name of Steader Dale Co. Inc. by (signature) Dale Bakren
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T R W D W SEC 24 NW 1/4 NE 1/4 NW 1/4