

1) LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Washington		SE 1/4 NW 1/4 NW 1/4	11	T 4 S	R 4
Distance and direction from nearest town or city street address of well if located within city?					
1 East of Greenleaf					
2) WATER WELL OWNER: Tom Brabec					
RR#, St. Address, Box # 130 Locust			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code Greenleaf, KS. 66943			Application Number:		
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 52 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 1.5 ft. below land surface measured on mo/day/yr 9/22/99			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 4.0 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 52 ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Livestock			
		Was a chemical/bacteriological sample submitted to Department? Yes No 8; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes * No			
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued * Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
		7 Fiberglass			
Blank casing diameter 5 in. to 32 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 24 in., weight 200 lbs./ft. Wall thickness or gauge No. 26 5					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 32 ft. to 52 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 52 ft., From ft. to ft.					
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 5 ft. to 25 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? South		How many feet? 30			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0 10 Brown Clay					
10 24 Yellow Clay					
24 32 Gray Shale					
32 39 Limestone Layers					
39 52 Red Shale					
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/22/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 518 This Water Well Record was completed on (mo/day/yr) 9/27/99 under the business name of Blue Valley Drilling by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					