

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Washington		SW 1/4 NE 1/4 SE 1/4	4	T 4 S	R 4 (E)W
Distance and direction from nearest town or city street address of well if located within city?					
North edge of Greenleaf					
2 WATER WELL OWNER: Ronald Laflen					
RR#, St. Address, Box # : 116 Pine St				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Greenleaf, KS 66943				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 145 ft. ELEVATION:			
N W E S NW NE SW SE *		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 69 ft. below land surface measured on mo/day/yr 9/24/03			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 20 gpm: Well water was ft. after hours pumping gpm			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial <u>7 Domestic (lawn & garden)</u> 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No * ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes * No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron		8 Concrete tile	
2 <u>PVC</u> 4 ABS		6 Asbestos-Cement		9 Other (specify below)	
		7 Fiberglass			
Blank casing diameter 5 in. to 135 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 18 in., weight 200 lbs./ft. Wall thickness or guage No. .265					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 <u>PVC</u> 10 Asbestos-Cement					
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)					
		9 ABS		12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 7 <u>Saw cut</u> 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
		7 Torch cut 10 Other (specify) ft.			
SCREEN-PERFORATED INTERVALS: From 135 ft. to 145 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 30 ft. to 145 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other					
Grout Intervals: From 5 ft. to 30 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? None		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Topsoil			
4	55	Tan Clay			
55	80	Yellow Fine Sand			
80	87	Sandy Clay (Silty)			
87	135	Sand (Very Fine)			
135	142	Sand (Fine-Med.)			
142	148	Gray Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/24/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 518 This Water Well Record was completed on (mo/day/yr) 10/3/03 under the business name of Blue Valley Drilling by (signature) <i>Eric Paul</i>					