

1 LOCATION OF WATER WELL: County: Washington		Fraction SE ¼ SE ¼ SE ¼	Section Number 4	Township Number T 4 S	Range Number R 4 EW
Distance and direction from nearest town or city street address of well if located within city? <u>5th & Main, Greenleaf, KS 66943</u>					
2 WATER WELL OWNER: Farmers Coop RR#, St. Address, Box # : P.O. Box 303 City, State, ZIP Code : Greenleaf, KS 66943 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N -NW--NE-- W---X---E -SW--SE-- S		4 DEPTH OF COMPLETED WELL 39.0 ft. ELEVATION: N.M. Depth(s) Groundwater Encountered 1. 34.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 36.18 ft. below land surface measured on mo/day/yr. 09/18/2003 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Product Recovery Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes (No)			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 44 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface N.M. in., weight lbs./ft. Wall thickness or gauge No. Sch 40 PVC TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 19 ft. to 39 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 17 ft. to 44 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 1 ft. to 17 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? Lust Site FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 20 Clay, silty, dry 20 44 Sand, very fine to fine					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, 2 reconstructed, or 3 plugged under my jurisdiction and was completed on (mo/day/year) 07/30/2003 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 574 This Water Well Record was completed on (mo/day/yr) 10/21/03 under the business name of Colorado Great Plains, Inc. by (signature) Meghan E. Quinn					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					