WATER WELL RECORD		Form W	WC-5	Di	ivision of Wate	r Resources App. N	o. L		
1 LOCATION OF WATER WELL: County: Washington		Fraction NE ¼ NE ¼ NE	1/4 NF 1/2		on Number 09	Township No. T 04 S	Range Number R 04 <b>☑</b> E  □W		
		dress of Well Location; i				System (GPS) ir			
	from nearest town or intersection: If at owner's address, check here .						Latitude:39.72565 (in decimal degrees)		
Main & 5th Street					Long	Longitude: 96.97561 (in decimal degrees)			
Greenleaf, KS					Eleva	Elevation: .1411.29  Datum:  WGS 84,  NAD 83,  NAD 27			
2 WA	TER WEL	L OWNER: Farmers	Cooperative Eleava	ator As		n: 🗾 wGS 84 ction Method:	4, ☐ NAD 83, ☐	NAD 27	
RR#, Street Address, Box #: PO Box 303						GPS unit (Make/Model:)			
City, State, ZIP Code : Greenleaf, KS 66943						☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey			
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m									
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 50.00 ft.									
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1).37.15 ft. (2)								
_	N WELL'S STATIC WATER LEVEL37.15ft. below land surface measured on mo/day/yr. 6-08-2016								
	Pump test data: Well water wasft. after hours pumpingg								
w   NY	1NW NE    0.60 · 60.00 ·								
"	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
	SW-1-SF Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Irrigation									
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No									
S If yes, mo/day/yr sample was submitted									
Water well disinfected: Tes W 140									
5 TYPE OF CASING USED: Steel PVC Other									
Casing diameter .2.38 in. to .50 ft., Diameter in. to ft., Diameter in. to ft.									
Casing height above land surface0.29 in., Weight									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel									
Brass Galvanized Steel None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:  Continuous slot  Mill slot  Gauze wrapped  Torch cut  Drilled holes  None (open hole)									
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
From									
6 GROUT MATERIAL: Neat cement Cement grout Pentonite Other Grout Intervals: From 1 ft. to 33 ft., From ft. to ft., From ft. to ft.									
Grout Ir	ntervals:	From .1 ft. to	33 ft., From		. ft. to	ft.,	From	. ft. toft.	
What is the nearest source of possible contamination:									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock p☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☑ Fuel storage									
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well									
		well		T					
FROM	TO	LITHOLOG		FROM	ТО	LITHO. LO	OG (cont.) <u>or</u> PLU	IGGING INTERVALS	
27		Clay, silty, light brown ( ilt, clayey, light brown				MW35			
21	30 3	iii, ciayey, light brown	IVIC			1111100			
							VOTES (1971-1971-1971-1971-1971-1971-1971-1971		
		₹					***************************************		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged									
under my jurisdiction and was completed on (mo/day/year) .5-25-2016 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 594 This Water Well Record was completed on (mo/lay) vely 06-22-2016 under the business name of Coranco Great Plains, Inc. by (signature)									
		se typewriter or ball point pen						answers. Send one copy to	
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.									
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html									