

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: WASHINGTON		NW 1/4 SW 1/4 SE 1/4	9	T 4 S	R 5 EW
Distance and direction from nearest town or city street address of well if located within city? 60 FEET NORTH OF 2ND AVE					
2 WATER WELL OWNER: USDA/ACC					
RR#, St. Address, Box # : STOP 0513- ROOM 4725			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : WASHINGTON DC 20250			Application Number: N/A		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 126 ft. ELEVATION:			
N - - NW - - NE - - W - - - - E - - SW - - SE - - S X		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well			
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes (NO)					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped		6 Asbestos-Cement 9 Other (specify below) Welded			
2 PVC 4 ABS 7 Fiberglass		Threaded FLUSH			
Blank casing diameter 2 in. to 116 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement		8 RMP (SR) 11 Other (Specify)			
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 126 ft. to 116 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 126 ft. to 114 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other CONCRETE					
Grout Intervals: From 114 ft. to 109 ft., From 109 ft. to 5 ft., From 5 ft. to 0 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	BRN SILT			
10	116	BRN CLAY W/ SHALE			
116	125	BRN F SAND			
125	126	LIMESTONE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/06/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 658 This Water Well Record was completed on (mo/day/yr) 01/11/07 under the business name of BOART LONGYEAR COMPANY by (signature) Michael May					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					