al degrees) NAD 27									
E W ce and here: al degrees) al degrees) NAD 27									
al degrees) al degrees) NAD 27									
al degrees) al degrees) NAD 27									
al degrees) NAD 27									
al degrees) NAD 27									
al degrees) NAD 27									
al degrees) NAD 27									
NAD 27									
ист .									
PS (unit make/model: MAGELLAN EXPLORIST) (WAAS enabled? ☐ Yes ☐ No)									
· (WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map									
Online Mapper:									
I □ TOC									
Land Survey GPS Topographic Map Other									
Supply: lease									
☐ Geotechnical									
d Loop ☐ Horizontal ☐ Vertical Loop ☐ Surface Discharge ☐ Inj. of Water									
4. Industrial Recovery Injection 13. Other (specify):									
Water well disinfected? ☐ Yes ☐ No 8 TYPE OF CASING USED: ☐ Steel ■ PVC ☐ Other									
hreaded									
Casing diameter 5 in to 42 ft., Diameter in to ft., Diameter in to ft. Diameter in to ft. Casing height above land surface 18 in Weight 2.8 lbs./ft. Wall thickness or gauge No. 265									
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)									
ft.									
ft.									
☐ Other (Specify) Direction from well? NONE PRESENT Distance from well? ft.									
ERVALS									
-ATTO									
plugged									
belief.									
2015									