

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
	County: Marshall	SE 1/4 SE 1/4 SW 1/4	28	T 4 S	R 8 (E/W)

Distance and direction from nearest town or city street address of well if located within city?

HWY 77 & HWY 9; 5 East, 1 South & 1/2 East

2	WATER WELL OWNER: M. F. King	Board of Agriculture, Division of Water Resources
	RR#, St. Address, Box # : 5819 Bluebridge	Application Number:
	City, State, ZIP Code : Wichita, KS 67208	

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL 60 ft. ELEVATION:
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 32 ft. below land surface measured on mo/day/yr 9/17/04 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 2.2 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes No * ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes * No	

5	TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued * Clamped
	1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
	2 PVC	4 ABS	7 Fiberglass	Threaded
Blank casing diameter 5" in. to 16" ft., Dia 10 in. to 36 ft., Dia in. to ft.				
Casing height above land surface 30 in., weight 200 lbs./ft. Wall thickness or gauge No. 265				
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-Cement	
1 Steel		3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass		4 Galvanized Steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:		5 Guazed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS: From 36 ft. to 56 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 16 ft. to 60 ft., From ft. to ft.				

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 3' ft. to 16' ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? SW		How many feet? 100			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8	Brown Clay			
8	22	Tan Shale & Limestone			
22	30	Red Shale			
30	37	Tan Shale			
37	39	Yellow Limestone			
39	62	Gray Shale			

RECEIVED

OCT 06 2004

BUREAU OF WATER

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/17/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 518 This Water Well Record was completed on (mo/day/yr) 9/30/04 under the business name of Blue Valley Drilling by (signature) <i>[Signature]</i>
---	--