USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County	Fraction		Section number		Township number	Range number		
	Marshall	SE 1/4 SE 1/4 SE	1/4	18	8	T 4 s	r 8	(E)W	
2. Distance and direction from nearest town or city: 5 Mi E 1 Mi N R Blue Rapids, KS				3. Owner of well: Charles J. Hula					
Street address of well location if in city:					or street: Rt 1 or strate, zip code: Blue Rapids, KS., 66411				
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia. 8" in. Completion date 10/23/79 Well depth 101 ft.			
N						7 Cable tool X Rotary Driven Dug			
						Hollow rod Jetted Bored Reverse rotary			
						8. Use: X Domestic - Public supply Industry Irrigation Air conditioning Stock			
11						LawnOil field water Other			
SW SE						9. Casing: Material Height: Above or below Threaded Welded Surface 1.2 in.			
S						Threaded Welded Surface in. RMP PVC Weight lbs./ft.			
1 Mile → 1				From	То	Dia 5 in. to 101 ft. depth Wall Thickness: inches or Diain. to ft. depth gage No			
5. Type and color of material				110111	"	10. Screen: Manufacturer's name Plastic nsi approved			
Soil Top				0	2	Type Plastic Die 5"			
Clay Tan and Yellow				2	12	Slot/gauze 045 Length 20 Set between 76 ft. and 96 ft.			
Limestone				12	15	Gravel pack? X Size range of material 18=1			
				1		11. Static water level: mo./day/yr.			
Shale yellow				15		75 ft. below land surface Date 10/23/79			
Shale & Limestone layers				17	34	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m. 13. Water sample submitted: mo./day/yr.			
Shale Gray & Brown				34	54				
Limestone				54	56				
Shale Gray				56	66	Yes X No Date			
Shale Blue				66	73	Pitless adapter Inches above grade 15. Well grouted? Bentonite Concrete Depth: From ft. to ft. 16. Nearest source of possible contamination: ft 500 Direction TypeHoghous e Well disinfected upon completion? Yes No 17. Pump: Not installed Manufacturer's name Not installed			
Shale Gray					80				
				+	 				
Shale Brown				80	86				
Shale Gray				86	89				
Shale Brown				89	93				
Shale Gray & Tan				93	99	Model number HP Volts			
Rock Hard				99	100	Type: Submersible	Turbin		
Shale Gray (Use a second sheet if needed)				100	101	Jet Centrifugal	Recipr	ocating S	
18. Elevation:	19. Remarks:	······································		•	•	20. Water well contractor's c	ertification:		
						This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Topography:					Blue Valley Drilling 2341 2				
X Slope						Business Bue Rapids KS 66411 No.			
Upland Signed Signed							Date esentative	3.28-80 5	
								, <i>\mathcal{W}</i>	