


1 LOCATION OF WATER WELL: County Marshall Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 5 Township Number T 4 S Range Number R 9 E/W

Distance and direction from nearest town or city street address of well if located within city?

1 North 1/2 West of Frankfort, Kansas 66427

2 WATER WELL OWNER Arvin Jones
 RR#, St. Address, Box # : R.R. #1 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Frankfort, Kansas. 66427 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 142 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 1 ft. 2. 1 ft. 3. 1 ft.
 WELL'S STATIC WATER LEVEL 70 ft. below land surface measured on 6-15-1985
 Pump test data: Well water was 100 gpm. Well water was 128 ft. after 8 hours pumping 140 gpm
 Est. Yield 100 gpm. Well water was 128 ft. after 8 hours pumping 140 gpm
 Bore Hole Diameter 128 in. to 128 ft., and 8 in. to 140 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes None No None; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes None No None

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 5 ft., Dia 5 in. to 5 ft., Dia 5 in. to 5 ft.
 Casing height above land surface 200 lbs./ft. Wall thickness or gauge No. 200
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft. From 10 ft. to 140 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 140 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 140 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? WEST How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	1	Top soil			
1	3	Brown clay			
3	87	Tan clay			
87	116	Blue clay			
116	124	Tan clay			
124	128	Gravel			
128	142	Lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-15-1985 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 234d This Water Well Record was completed on (mo/day/yr) 6-28-85 under the business name of Blue Valley Drilling by (signature) Arnold Strader

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.