

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>WASH.</u>		<u>NE 1/4 NW 1/4 NE 1/4</u>	<u>23</u>	T <u>5</u> S	R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>3 north 1/2 W Clifton,</u>					
2 WATER WELL OWNER: <u>MARVIN BACON INC.</u>			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: <u>RR#1</u>			Application Number:		
City, State, ZIP Code: <u>Clifton, Kansas 66937</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>120</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>90</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>80</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>35</u> gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>5</u> in. to <u>120</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		☒ 1 Domestic ☒ 7 Public water supply ☐ 8 Air conditioning ☐ 11 Injection well ☐ 2 Irrigation ☐ 4 Industrial ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>X</u> No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped ☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded					
Blank casing diameter <u>5</u> in. to <u>100</u> ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface <u>12</u> in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass ☒ 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped ☒ 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>100</u> ft. to <u>120</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>120</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other					
Grout Intervals: From <u>0</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens ☒ 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>west</u> How many feet? <u>40</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TOPSOIL			
3	26	CLAY			
26	64	CLAYED CLAY			
64	78	YELLOW CLAY			
78	120	SHANDOCK			
120		Stopped.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-23-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>361</u> This Water Well Record was completed on (mo/day/yr) <u>6-23-96</u> under the business name of <u>Cox-Beswick Inc. SERV.</u> by (signature) <u>David Beswick</u>					