

MW-6

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Washington</u>		<u>SW</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$	<u>35</u>	<u>T 5 S</u>	<u>R 1 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>119 E. Paralle</u>					
2 WATER WELL OWNER: <u>Cabwells b6</u>					
RR#, St. Address, Box #: <u>PO Box 164</u>					
City, State, ZIP Code: <u>Clifton 66937</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>35.5</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1</u> ft. <u>~30</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>28.3</u> ft. below land surface measured on mo/day/yr <u>11/1/99</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8.625</u> in. to <u>35.5</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>MW-6</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u>					
Blank casing diameter <u>2</u> in. to <u>20.5</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>Flush</u> in., weight <u>sch 40</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>35.5</u> ft. to <u>20.5</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>35.5</u> ft. to <u>19</u> ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: <u>3</u> From <u>19</u> ft. to <u>17</u> ft., From <u>17</u> ft. to <u>0</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) <u>contaminated sub</u>					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	Asphalt			
1.5	5	Silty clay			
5	10	clayey silt			
10	19	silty clay			
19	35.5	Silty some clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>11/1/99</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>585</u> This Water Well Record was completed on (mo/day/yr) <u>11/1/99</u> under the business name of <u>FEI</u> by (signature) <u>Adam RDS</u>					