


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Washington	SE ¼ NE ¼ NW ¼	11	T 5 S	R 1 E/W

Distance and direction from nearest town or city street address of well if located within city?

5 miles North & 1/2 Mile West of Clifton, KS

2 WATER WELL OWNER: John Leiszler	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 417 Deer Rd.	Application Number:
City, State, ZIP Code: Clifton, KS 66937	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 155 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 69 ft. below land surface measured on mo/day/yr 4/18/01
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 800 gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 5 in. to 1.65 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering ☒ Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Irrigation Test
	Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
☒ PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 2.5 in. to 135 ft., Dia			11 Other (specify)
Casing height above land surface 24 in., weight 657 lbs./ft. Wall thickness or gauge No. 110			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	☒ Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 135 ft. to 155 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 25 ft. to 155 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	☒ Bentonite	4 Other
Grout Intervals: From 3 ft. to 25 ft., From ft. to ft.				
What is the nearest source of possible contamination: None within 1/2 mile	10 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	13	Clay, gray			
13	28	Clay, Sandy, Brown			
28	32	Rock, sand			
32	35	Shale, red, soft			
35	40	Shale, gray, soft			
40	41	Shale, red & white, soft			
41	42	Shale, yellow, soft			
42	59	Sandstone			
59	84	Shale, gray			
84	154	Sandstone, very loose			
154	165	Shale, gray			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/19/01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 4/20/01 under the business name of Peterson Irrigation, Inc. by (signature) <i>Mike Peterson</i>
--