

1 LOCATION OF WATER WELL: County: Washington	Fraction: NE 1/4 NE 1/4 NW 1/4	Section Number: 10	Township Number: T 5 S	Range Number: R 1 E/WX
---	---------------------------------------	---------------------------	-------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 mile west and 4 miles north of Clifton, KS

2 WATER WELL OWNER: John Leiszler RR#, St. Address, Box # : 417 Deer Rd. City, State, ZIP Code : Clifton, KS 66937	Board of Agriculture, Division of Water Resources Application Number: 44,502
---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 220 ft. ELEVATION:
--	---

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL **42** ft. below land surface measured on mo/day/yr **3/10/03**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield **1000-1200** Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

☒ Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
☒ PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 1.6 in. to 1.20 ft., Dia in. to ft., Dia in. to ft.			
Casing height above land surface 12 in., weight 16.15 lbs./ft. Wall thickness or gauge No. 500			
TYPE OF SCREEN OR PERFORATION MATERIAL:	☒ PVC	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
☒ Mill slot	7 Torch cut	10 Other (specify)	
2 Louvered shutter			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From 120 ft. to 220 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 23 ft. to 220 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	☒ Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 23 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: None within 1/4 mile	10 Livestock pens	14 Abandoned water well		
1 Septic tank	11 Fuel storage	15 Oil well/Gas well		
2 Sewer lines	12 Fertilizer storage	16 Other (specify below)		
3 Watertight sewer lines	13 Insecticide storage			
4 Lateral lines				
5 Cess pool				
6 Seepage pit				
7 Pit privy				
8 Sewage lagoon				
9 Feedyard				
Direction from well?	How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	13	Clay, gray			
13	28	Shale, gray & red			
28	75	Sandstone, red			
75	83	Shale, light gray			
83	85	Iron pyrite			
85	109	Shale, gray			
109	190	Sandstone, fine to medium			
190	220	Sandstone, medium to coarse			
220	222	Rock, hard			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/10/03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 138 This Water Well Record was completed on (mo/day/yr) 3/24/03 under the business name of Peterson Irrigation, Inc. by (signature) <i>Mike Peterson</i>
--