


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County WASHINGTON	Fraction SW 1/4 SW 1/4 SW 1/4 NW 1/4 NW 1/4 NW 1/4	Section number 30	Township number T 5 S R 1 E W	Range number 1
2. Distance and direction from nearest town or city: 2 E 1/4 S				3. Owner of well: LOWELL + LOIS TOBYNE		
Street address of well location if in city: CLYDE, KANSAS				R.R. or street: RR		
				City, state, zip code: CLIFTON, KANSAS		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 22 in. Completion date 2/13/74		
				Well depth 112 ft.		
				7. ☐ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary		
				8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
				9. Casing: Material AL Height: Above or below Threaded ☐ Welded ☐ Surface 15 in. RMP ☐ PVC ☐ Weight 30 lbs./ft. Dia. 12 in. to 12 ft. depth Wall Thickness: inches or Dia. 34 in. to 34 ft. depth gage No. 34		
5. Type and color of material		From	To	10. Screen: Manufacturer's name JOHANSON		
topsoil (silty)		0	3	CONCRETE		
silty sand		7	18	Type ASBESTOS Dia. 12		
sand		18	27	Slot/gauge 1/4" Length 39		
poor gravel (fine)		27	30	Set between 73 ft. and 112 ft.		
Rock layer in sand		30	35	Gravel pack? ☒ Size range of material 1/4" X 1/2"		
Sandrock		35	53	11. Static water level: 23 ft. below land surface Date 2/13/74		
gray clay		53	54	12. Pumping level below land surfaces: 100 ft. after 1 hrs. pumping 400 g.p.m. 54 ft. after 1 hrs. pumping 400 g.p.m. Estimated maximum yield 400 g.p.m.		
clay w/ rock layers		54	56	13. Water sample submitted: Yes ☒ No ☐ Date 2/13/74		
Sandrock		56	113	14. Well head completion: Yes ☒ Pitless adapter ☐ X Inches above grade		
stop (blue shale)		113		15. Well grouted? Yes ☒ With: ☐ Neat cement ☐ Bentonite ☒ Concrete X Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: ft. 10 Direction NE Type 10 Well disinfected upon completion? Yes ☒ No ☐		
				17. Pump: Not installed Manufacturer's name WESTERN LAND Model number 310K/H HP 35 Volts 258 Length of drop pipe 100 ft. capacity 400 g.p.m. Type: ☐ Submersible ☒ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. GEORGE + SONS INC 258 Business name License No. Address CLIFTON, KANSAS Signed David By Date 2/13/74 Authorized representative		
18. Elevation: 1283'		19. Remarks: Well is in extreme SW corner across railroad				
Topography: ☐ Hill ☐ Slope ☒ Upland ☐ Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5