


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 33 Township Number T 5 S Range Number R 14 EW  
 County: Nemaha

Distance and direction from nearest town or city street address of well if located within city?  
2 1/8 mi 2 3/4 East of Bancroft

2 WATER WELL OWNER: Ron Thonen  
 RR#, St. Address, Box #: 8205 286th Rd Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Circleville, KS 66416 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 98' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 1 ft. 2. 1 ft. 3. 1 ft.  
 WELL'S STATIC WATER LEVEL: 40' ft. below land surface measured on mo/day/yr 5/22/00  
 Pump test data: Well water was 5.0 gpm ft. after 5 hours pumping  
 Est. Yield 5.0 gpm Well water was 5.0 gpm ft. after 5 hours pumping  
 Bore Hole Diameter: 12" in. to 12" in. and 12" in. to 12" in.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
 2 PVC 4 ABS 7 Fiberglass Threaded  
 Blank casing diameter 5" in. to 0-16' ft., Dia 5" in. to 26-70' ft., Dia 5" in. to 85-97' ft.  
 Casing height above land surface 24" in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 16' ft. to 26' ft., From 97' ft. to 98' ft.  
 From 70' ft. to 85' ft., From 97' ft. to 98' ft.  
 GRAVEL PACK INTERVALS: From 14' ft. to 98' ft., From 97' ft. to 98' ft.  
 From 97' ft. to 98' ft., From 97' ft. to 98' ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0' ft. to 14' ft., From 97' ft. to 98' ft., From 97' ft. to 98' ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? East How many feet? 50'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top soil			
4	15	Clay-brown			
15	18	FS-brown			
18	21	Silty Clay-brown			
21	23	FS-Brown dirty			
23	37	Clay-brown			
37	52	Clay-black			
52	65	FS-silty brown			
65	70	clay-black silty			
70	82	FS-CS-med gravel			
82	92	Clay-black			
92	93	boulders			
93	98	Clay-black			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/22/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 5-31-00 under the business name of Strader Drilling Co., INC. by (signature) Dale Strader