


1 LOCATION OF WATER WELL: Fraction SW 1/4 SE 1/4 NE 1/4 Section Number 8 Township Number T 5S S Range Number R 15E E/W
 County: JACKSON

Distance and direction from nearest town or city street address of well if located within city?

1 1/2 west, 2 north of Netawaka

2 WATER WELL OWNER: Ernest Finger
 RR#, St. Address, Box #: Rt. 1 Box 150 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Wetmore, KS 66550 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 118' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 90' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 68' ft. below land surface measured on mo/day/yr 01-06-97
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 5 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter 12" in. to ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5" in. to 0-83 ft., Dia 5" in. to 93-117 ft., Dia in. to ft.
 Casing height above land surface 24 in., weight 2.82 lbs./ft. Wall thickness or gauge No. 258
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled Holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 83 ft. to 93 ft., From ft. to ft.
 From 117 ft. to 118 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 118 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? north How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	26	Clay-Brown			
26	50	Clay-Blue			
50	51	Boulders			
51	66	Clay-Blue			
66	67	Boulders			
67	81	Clay-Blue			
81	85	FS-CS-Brown			
85	90	FS-CS-Med-Gravel-Brown 1/4x3/8			
90	104	Shale-Grey			
104	105	Limestone-Grey			
105	115	Shale-Grey			
115	118	Limestone-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/06/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 2-3-97 under the business name of STRADER DRILLING CO., IONC. by (signature) Dale Askren