


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 NE 1/4 Section Number 29 Township Number T 5 S Range Number R 16E EW

County: JACKSON Distance and direction from nearest town or city street address of well if located within city? 1 1/2 west of Whiting

2 WATER WELL OWNER: Larry Amon RR#, St. Address, Box #: 202 Superior St. City, State, ZIP Code: Netawaka, KS 66516 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL... 60' ft. ELEVATION: ... Depth(s) Groundwater Encountered 1... 10-15' ft. 2... ft. 3... ft. WELL'S STATIC WATER LEVEL... 1' ft. below land surface measured on mo/day/yr... 6-21-94 Pump test data: Well water was... ft. after... hours pumping... gpm Est. Yield... 40 gpm: Well water was... ft. after... hours pumping... gpm Bore Hole Diameter... 12" in. to... ft., and... in. to... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes... No... X...; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped Welded Threaded Blank casing diameter... 5" in. to... 0-10 ft., Dia... 5" in. to... 20-59 ft., Dia... in. to... ft. Casing height above land surface... 24" in., weight... 2.82 lbs./ft. Wall thickness or gauge No... 258 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) SCREEN-PERFORATED INTERVALS: From... 10 ft. to... 20 ft., From... ft. to... ft. From... 59 ft. to... 60 ft., From... ft. to... ft. GRAVEL PACK INTERVALS: From... 9 ft. to... 60 ft., From... ft. to... ft. From... ft. to... ft., From... ft. to... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From... 0 ft. to... 9 ft., From... ft. to... ft., From... ft. to... ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) drainage ditch Direction from well? west How many feet? 100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	10	Clay-Grey			
10	15	Fine Sand-Coarse Sand-Med-Pea Gravel 1/2x1/2-Brown			NOTE: Permission to shallow grout from Richard Taylor 6-23-94
15	59	Clay-Brown			
59	60	Shale-Grey			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-21-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182 This Water Well Record was completed on (mo/day/yr) 7-19-94 under the business name of STRADER DRILLING CO., INC. by (signature) Dale Strader