


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: ATCHISON Fraction: NE $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$ Section Number: 33 Township Number: T 5 S Range Number: R 17 EW

Distance and direction from nearest town or city street address of well if located within city? 1/2 N 1/4 E 1/2 N MUSCOTA

2 WATER WELL OWNER: DALE BODEN HAUSEN RR#, St. Address, Box #: 221 Board of Agriculture, Division of Water Resources City, State, ZIP Code: MUSCOTA, KANSAS 66058 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 89 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 55 ft. below land surface measured on mo/day/yr 12-23 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 15 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 10 in. to 20 ft., and 8 in. to 90 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Heavy Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter 6.578 in. to 110 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 0.255 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 90 ft. to 110 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 110 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite grout 4 Other Grout Intervals: From 4 ft. to 18 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South How many feet? 50

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0	6	TOP SOIL			
6	50	Yellow CLAY			
50	89	Blue CLAY (SANDY)			
89	92	SOFT LIME STONE			
92	110	Blue SHALE			

dry
furnace
could tell
where it is

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-23-78 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 317 This Water Well Record was completed on (mo/day/yr) 6-24-81 under the business name of Williamson Well Drilling by (signature) Francis Kramer

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.