

1 LOCATION OF WATER WELL:		Fraction	SE	SE	SW	Section Number	Township Number	Range Number
County: <u>ATCHISON</u>		SW 1/4	SW 1/4	SW 1/4	<u>1</u>	T <u>5</u> S	R <u>18</u> E/W	
Distance and direction from nearest town or city street address of well if located within city?								

2 WATER WELL OWNER: HURON CHRISTIAN Church
RR#, St. Address, Box # :
City, State, ZIP Code : HURON, KANSAS

Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile		N	
		W	E
SW	SE	NE	NW
S			

4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION: 50 ft.

Depth(s) Groundwater Encountered 1. 50 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr 12-19

Pump test data: Well water ft. after hours pumping gpm

Est. Yield 3 gpm: Well water ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 20 ft., and 8 in. to 50 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	7 Lawn and garden only
3 Feedlot	6 Oil field water supply	9 Dewatering
10 Observation well	12 Other (Specify below)	

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input type="checkbox"/>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <input type="checkbox"/>
		7 Fiberglass		Threaded <input type="checkbox"/>

Blank casing diameter 6 in. to 70 ft., Dia. in. to . ft., Dia. in. to . ft.

Casing height above land surface 18 in., weight . lbs./ft. Wall thickness or gauge No. 0.255

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From 6.5 ft. to 70 ft.

GRAVEL PACK INTERVALS: From 30 ft. to 70 ft., From . ft. to . ft.

9 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite grout Other

Grout Intervals: From 4 ft. to 15 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
<u>3 Watertight sewer lines</u>	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? EAST How many feet? 75 ft

[illegible]

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-19-77 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 317 This Water Well Record was completed on (mo/day/yr) 6-22-81 under the business name of Williamson Well Drig by (signature) Frank Kramer

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.