

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Washington		NE 1/4 SW 1/4 SW 1/4	11	T 5 S	R 2 (E/W)
Distance and direction from nearest town or city street address of well if located within city? 1 1/4 West, 1/2 South, 1/2 West & 1/4 North of Palmer					
2 WATER WELL OWNER: Troy Damman					
RR#, St. Address, Box # : 601 3rd St			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : AXTELL Axtell, KS 66403			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 1.00 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 3 ft. 3 4 ft. WELL'S STATIC WATER LEVEL 5.8 ft. below land surface measured on mo/day/yr 4/30/07 Pump test data: Well water was 40 gpm. Well water was 40 gpm. Well water was 40 gpm. Est. Yield 40 gpm. Well water was 40 gpm. Well water was 40 gpm. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Livestock			
Was a chemical/bacteriological sample submitted to Department? Yes * No * ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes * No					
5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued * Clamped 1 Steel 3 RMP (SR) 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded Blank casing diameter 5 in. to 80 ft. Dia 80 in. to 80 ft. Dia 80 in. to 80 ft. Dia 80 in. to 80 ft. Dia Casing height above land surface 1.8 in., weight 200 lbs./ft. Wall thickness or gauge No. 26.5 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guaged wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 8 Saw cut SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft. From 80 ft. to 100 ft. From 80 ft. to 100 ft. From 80 ft. to 100 ft. GRAVEL PACK INTERVALS: From 30 ft. to 100 ft. From 30 ft. to 100 ft. From 30 ft. to 100 ft. From 30 ft. to 100 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5 ft. to 30 ft. From 5 ft. to 30 ft. From 5 ft. to 30 ft. From 5 ft. to 30 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? None Present How many feet?					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/30/07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 5.18 This Water Well Record was completed on (mo/day/yr) 5/10/07 under the business name of Blue Valley Drilling by (signature) Eric Stender					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					