

USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

Section 29 is not 640 acres.
Maps are not clear except for the West line of Section 29.
We think this is the correct legal description.

WATER WELL RECORD
KSA 82a-1209-1215

Kansas Department of Health and
Environment—Division of Environment
Water well Contractors
Topeka, Kansas 66620

Hilary Heim for St. Benedict's Abbey

1. Location of well:	County Atchison	Fraction SW NW NE 1/4 1/4 1/4	Section number 29	Township number T 5	Range number S R 21 E
2. Distance and direction from nearest town or city: Atchison, KS 1 3/4 NE from			3. Owner of well: St. Benedict's ABBEY		
Street address of well location if in city:			R.R. or street:		
			City, state, zip code: Atchison, Kansas 66002		

4. Locate with "X" in section below: Road Sketch map:		6. Bore hole dia. 30 in. Completion date 6-10-76																																		
		Well depth 52 ft.																																		
5. Type and color of material		7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary																																		
<table border="1"> <thead> <tr> <th></th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>Top Soil</td> <td>0</td> <td>1</td> </tr> <tr> <td>Fine brown sand</td> <td>1</td> <td>2</td> </tr> <tr> <td>Gray clay</td> <td>2</td> <td>9</td> </tr> <tr> <td>Fine brown sand</td> <td>9</td> <td>11</td> </tr> <tr> <td>Med. gray sand & clay</td> <td>11</td> <td>15</td> </tr> <tr> <td>Small gray gravel & fine sand & gray clay</td> <td>15</td> <td>32</td> </tr> <tr> <td>Medium brown gravel</td> <td>32</td> <td>60</td> </tr> <tr> <td>Very fine gravel</td> <td>60</td> <td>67</td> </tr> <tr> <td>Caved back to</td> <td>52</td> <td></td> </tr> <tr> <td>Stopped</td> <td>52</td> <td></td> </tr> </tbody> </table>			From	To	Top Soil	0	1	Fine brown sand	1	2	Gray clay	2	9	Fine brown sand	9	11	Med. gray sand & clay	11	15	Small gray gravel & fine sand & gray clay	15	32	Medium brown gravel	32	60	Very fine gravel	60	67	Caved back to	52		Stopped	52		8. Use: Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other <input type="checkbox"/>	
	From	To																																		
Top Soil	0	1																																		
Fine brown sand	1	2																																		
Gray clay	2	9																																		
Fine brown sand	9	11																																		
Med. gray sand & clay	11	15																																		
Small gray gravel & fine sand & gray clay	15	32																																		
Medium brown gravel	32	60																																		
Very fine gravel	60	67																																		
Caved back to	52																																			
Stopped	52																																			
		9. Casing: Material Trans Height: (Above or below) 24 in. Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface <input type="checkbox"/> RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 16 in. to 26 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gauge No. 7/8																																		
		10. Screen: Manufacturer's name Johnson Well Co. Type Transite Dia. 16" (Slot) gauze 1/8x8 Length 26" Set between 26 ft. and 52 ft. ft. and <input type="checkbox"/> ft. Gravel pack yes Size range of material 5/8																																		
		11. Static water level: <input type="checkbox"/> mo./day/yr. 4 ft. below land surface Date 6-10-76																																		
		12. Pumping level below land surfaces: 17 ft. after 1 hrs. pumping 1000 g.p.m. 21 ft. after 3 hrs. pumping 2000 g.p.m. Estimated maximum yield 2500 g.p.m.																																		
		13. Water sample submitted: <input type="checkbox"/> mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date <input type="checkbox"/>																																		
		14. Well head completion: <input type="checkbox"/> Pitless adapter <input type="checkbox"/> Inches above grade																																		
		15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 20 ft.																																		
		16. Nearest source of possible contamination: ft. 2000 Direction South Type river Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																		
		17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name <input type="checkbox"/> Model number <input type="checkbox"/> HP <input type="checkbox"/> Volts <input type="checkbox"/> Length of drop pipe <input type="checkbox"/> ft. capacity <input type="checkbox"/> g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																		
18. Elevation: 790		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Hoobler Drilling Co. 323 Business name License No. Address St. Marys, KS, 66536 Signed Don Hoobler Date 6-16-76 Authorized representative																																		
19. Remarks: We do not install pumps.																																				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5