

WATER WELL RECORD Form WWC-5

MW2

Division of Water Resources App. No.

Well ID

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Atchison Fraction 1/4 NW 1/4 SW 1/4 NW 1/4 Section Number 30 Township Number T 5 S Range Number R 21 E W

2 WELL OWNER: Last Name: Business: Kansas Dept. of Collections Address: 714 Jackson; Suite 300 City: Topeka State: Ks. ZIP: 66603 Street or Rural Address where well is located: 1900 N. 2nd Str. Atchison, Ks.

3 LOCATE WELL WITH "X" IN SECTION BOX: N W E S 1 mile

4 DEPTH OF COMPLETED WELL: 45' Depth(s) Groundwater Encountered: 1) 37' 2) ... WELL'S STATIC WATER LEVEL 35.40' below land surface, measured on (mo-day-yr) 7/14/14

5 Latitude: 39.352563 Longitude: 95.064789 Datum: WGS 84 Source for Latitude/Longitude: Google Earth 6 Elevation: 1080.14' Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID Dewatering: how many wells? Aquifer Recharge: well ID Monitoring: well ID Environmental Remediation: well ID Air Sparge Soil Vapor Extraction Recovery Injection Oil Field Water Supply: lease Test Hole: well ID Cased Uncased Geotechnical Geothermal: how many bores? Closed Loop Horizontal Vertical Open Loop Surface Discharge Inj. of Water Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted: Water well disinfected? Yes No

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter: 2.375 in. to 2.5 ft. Diameter in. to ft. Diameter in. to ft. Casing height above land surface: 10 in. Weight lbs./ft. Wall thickness or gauge No. 5/8" x 40' TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 45' ft. to 25' ft. GRAVEL PACK INTERVALS: From 45' ft. to 23' ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other concrete Grout Intervals: From 23' ft. to 2' ft. From 2' ft. to 0' ft. From ft. to ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage tanks Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? South Distance from well? 75' ft.

10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	13.0	Med. Bensittly clay			
13.0	22.0	Yellow Bun - Rust Bun sandy clay till			
22.0	26.0	Rust Bun clayey sand			
26.0	45.0	Rust Bun sand			

Notes:

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 7/10/14 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 7322 This Water Well Record was completed on (mo-day-year) 7/10/14 under the business name of G.B. Environmental Drilling (James Burke)