

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Washington	NE ¼ NW ¼ NE ¼	22	T 5 S	R 3 (B/W)

Distance and direction from nearest town or city street address of well if located within city?
1½ South of Palmer on HWY 15, 2½ East

2 WATER WELL OWNER: Elmer Voelker	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 806 S Main	Application Number:
City, State, ZIP Code : Linn, KS 66953	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL **30** ft. below land surface measured on mo/day/yr **11/12/04**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield **6** gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)

Livestock

Was a chemical/bacteriological sample submitted to Department? Yes No *****; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ***** No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued * Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter 5" in. to 30' ft., Dia			
Casing height above land surface 18 in., weight 200 lbs./ft.			Wall thickness or gauge No. .265

TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-Cement	12 None used (open hole)
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS		
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			

SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			

SCREEN-PERFORATED INTERVALS:	From 32' ft. to 52' ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From 25 ft. to 60 ft.	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 5 ft. to 25 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? SE			How many feet? 200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Topsoil			
2	22	Tan Clay			
22	38	Tan Clay & Sandstone			
38	44	Sandstone			
44	62	Red Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1) constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/12/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 518 This Water Well Record was completed on (mo/day/yr) 11/25/04 under the business name of Blue Valley Drilling by (signature) <i>Elmer Voelker</i>
--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.