

1 LOCATION OF WATER WELL: County: Marshall Fraction E2 + S2 Section Number 16 Township Number T 5 S Range Number R 8 EW

Distance and direction from nearest town or city street address of well if located within city? Take 99 south 5 miles out of Frankfort & Turn West on County Road & go 10 miles & Turn South & go 2 miles

2 WATER WELL OWNER: Benton Farms Board of Agriculture, Division of Water Resources  
 RR#, St. Address, Box #: RR #3 Box 34 Application Number:  
 City, State, ZIP Code: Frankfort Kansas 66427

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
	NW	NE	
W			E
	SW	SE	
			S

4 DEPTH OF COMPLETED WELL: 41' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 10' 18" ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL 10' 18" ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield 20 gpm Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 8 in. to 4 1/2 in. to in. to ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS:  Glued  Clamped  Welded  Screwed  Threaded  
 Blank casing diameter 5 1/2 in. to 30 ft. Dia. in. to ft. Dia. in. to ft.  
 Casing height above land surface 2 in., weight Sch. 40 lbs./ft. Wall thickness or gauge No.  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 3/1000 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)  
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft. From ft. to ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 20 ft. to 40 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout intervals: From 0 ft. to 20 ft. From ft. to ft. From Enviropipe ft. to ft.  
 What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines old in use NOT 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)  
 Direction from well? West How many feet? 100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	16	Brown clay			
16	24	Gravel (water)			
24	27	Rock			
27	31	Grey shale			
31	36	Rock			
36	40	Black shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  (1) constructed,  (2) reconstructed, or  (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/6/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/yr) 7/26/88 under the business name of Haldeman Well Drilling by (signature) Craig Haldeman CWD/PI

OFFICE USE ONLY  
T  
R  
EW  
SEC.