


1 LOCATION OF WATER WELL: County: <u>Pottawatomie</u>		Fraction <u>SW 1/4 SW 1/4 SE 1/4</u>	Section Number <u>14</u>	Township Number T <u>6</u> S	Range Number R <u>12</u> <u>EW</u>																																																																																										
Distance and direction from nearest town or city street address of well if located within city? <u>1/2 N 1 1/2 E of Havensville</u>																																																																																															
2 WATER WELL OWNER: Dale Ames RR#, St. Address, Box # : Rt. 1 City, State, ZIP Code : <u>Havensville, KS 66432</u> Board of Agriculture, Division of Water Resources Application Number:																																																																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: <div style="text-align: center;"></div>		4 DEPTH OF COMPLETED WELL: <u>120'</u> ft. ELEVATION: ft. Depth(s) Groundwater Encountered 1. <u>107'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>78'</u> ft. below land surface measured on mo/day/yr <u>8-17-87</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>40</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8"</u> in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No																																																																																													
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5"</u> in. to <u>0-105'</u> ft., Dia <u>5"</u> in. to <u>115-120'</u> ft., Dia in. to ft. Casing height above land surface <u>24"</u> in., weight <u>2.82</u> lbs./ft. Wall thickness or gauge No. <u>.258</u> TYPE OF SCREEN OR PERFORATION MATERIAL: <u>7 PVC</u> 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>105</u> ft. to <u>115</u> ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>120</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.																																																																																															
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout <u>3 Bentonite</u> 4 Other Grout Intervals: From <u>4</u> ft. to <u>20</u> ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>S</u> How many feet? <u>220</u> <table border="1" style="width:100%; border-collapse: collapse;"><thead><tr><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th><th>FROM</th><th>TO</th><th>LITHOLOGIC LOG</th></tr></thead><tbody><tr><td>0</td><td>2</td><td>Top Soil</td><td></td><td></td><td></td></tr><tr><td>2</td><td>13</td><td>Clay-Brown</td><td></td><td></td><td></td></tr><tr><td>13</td><td>22</td><td>Limestone-Yellow</td><td></td><td></td><td></td></tr><tr><td>22</td><td>27</td><td>Shale-Red</td><td></td><td></td><td></td></tr><tr><td>27</td><td>30</td><td>Limestone-Yellow</td><td></td><td></td><td></td></tr><tr><td>30</td><td>36</td><td>Shale-Grey</td><td></td><td></td><td></td></tr><tr><td>36</td><td>38</td><td>Limestone-yellow</td><td></td><td></td><td></td></tr><tr><td>38</td><td>53</td><td>Shale-Grey</td><td></td><td></td><td></td></tr><tr><td>53</td><td>60</td><td>Limestone-Grey</td><td></td><td></td><td></td></tr><tr><td>60</td><td>78</td><td>Shale-Grey</td><td></td><td></td><td></td></tr><tr><td>78</td><td>95</td><td>Shale-Red</td><td></td><td></td><td></td></tr><tr><td>95</td><td>106</td><td>Limestone-Grey</td><td></td><td></td><td></td></tr><tr><td>106</td><td>111</td><td>Shale-Black-Loose</td><td></td><td></td><td></td></tr><tr><td>111</td><td>120</td><td>Shale-Grey</td><td></td><td></td><td></td></tr></tbody></table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG	0	2	Top Soil				2	13	Clay-Brown				13	22	Limestone-Yellow				22	27	Shale-Red				27	30	Limestone-Yellow				30	36	Shale-Grey				36	38	Limestone-yellow				38	53	Shale-Grey				53	60	Limestone-Grey				60	78	Shale-Grey				78	95	Shale-Red				95	106	Limestone-Grey				106	111	Shale-Black-Loose				111	120	Shale-Grey			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG																																																																																										
0	2	Top Soil																																																																																													
2	13	Clay-Brown																																																																																													
13	22	Limestone-Yellow																																																																																													
22	27	Shale-Red																																																																																													
27	30	Limestone-Yellow																																																																																													
30	36	Shale-Grey																																																																																													
36	38	Limestone-yellow																																																																																													
38	53	Shale-Grey																																																																																													
53	60	Limestone-Grey																																																																																													
60	78	Shale-Grey																																																																																													
78	95	Shale-Red																																																																																													
95	106	Limestone-Grey																																																																																													
106	111	Shale-Black-Loose																																																																																													
111	120	Shale-Grey																																																																																													
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-17-87</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>182</u> This Water Well Record was completed on (mo/day/yr) <u>9-9-87</u> under the business name of <u>Strader Drilling Co., Inc.</u> by (signature) <u>Dale Baker</u> INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.																																																																																															