

1 LOCATION OF WATER WELL  
 County: JACKSON Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 39 Township Number T 6 S Range Number R 13 EW

Distance and direction from nearest town or city? 3.5 S of Solider Street address of well if located within city?


2 WATER WELL OWNER: Wilbur Wilson  
 RR#, St. Address, Box #: 932 Ohio Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Holtan, KS 66436 Application Number:

3 DEPTH OF COMPLETED WELL: 120 ft. Bore Hole Diameter: 8 in. to ... ft. and ... in. to ... ft.  
 Well Water to be used as:  
 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well  
 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 7 Lawn and garden only 10 Observation well  
 Well's static water level: 90 ft. below land surface measured on December month 9 day 1979 year  
 Pump Test Data: Well water was ... ft. after ... hours pumping ... gpm  
 Est. Yield: 20 gpm: Well water was ... ft. after ... hours pumping ... gpm

4 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued  Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
 7 Fiberglass Threaded  
 Blank casing dia: 5 in. to 80 ft. Dia ... in. to ... ft. Dia ... in. to ... ft.  
 Casing height above land surface: 29 in., weight 2.89 lbs./ft. Wall thickness or gauge No. 258  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
 12 None used (open hole)  
 Screen or Perforation Openings Are:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)  
 Screen-Perforation Dia: 5 in. to ... ft. Dia ... in. to ... ft. Dia ... in. to ... ft.  
 Screen-Perforated Intervals: From 80 ft. to 120 ft. From ... ft. to ... ft. From ... ft. to ... ft.  
 Gravel Pack Intervals: From 15 ft. to 120 ft. From ... ft. to ... ft. From ... ft. to ... ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grouted Intervals: From 40-10 ft. to ... ft. From ... ft. to ... ft. From ... ft. to ... ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank 4 Cess pool 7 Sewage lagoon 11 Fertilizer storage 14 Abandoned water well  
 2 Sewer lines 5 Seepage pit 8 Feed yard 12 Insecticide storage 15 Oil well/Gas well  
 3 Lateral lines 6 Pit privy 9 Livestock pens 13 Watertight sewer lines 16 Other (specify below)  
 Direction from well: North How many feet: 150 ? Water Well Disinfected? Yes  No  
 Was a chemical/bacteriological sample submitted to Department? Yes  No  If yes, date sample was submitted ... month ... day ... year: Pump Installed? Yes  No   
 If Yes: Pump Manufacturer's name ... Model No. ... HP ... Volts ...  
 Depth of Pump Intake ... ft. Pumps Capacity rated at ... gal./min.  
 Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on December month 4 day 1979 year  
 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 182  
 This Water Well Record was completed on December month 6 day 1979 year under the business name of Strader Drilling Co Inc by (signature) Dale Ashren

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	TOP SOIL			
3	25	CLAY			
25	90	SHALE, grey LIMESTONE			
90	92	LIMESTONE, WATER BEARING			
92	120	SHALE, qt			
		hard water			

  
 ELEVATION: 1150

Depth(s) Groundwater Encountered 1. 90 ft. 2. ... ft. 3. ... ft. 4. ... ft. (Use a second sheet if needed)

OFFICE USE ONLY  
 T  
 S  
 R  
 13  
 CW  
 SEC  
 37  
 SW 1/4 SW 1/4 NW 1/4