WATER WELL RECORD	Form W	WC-5	Division of Wate	er Resources App. N	о.	
1 LOCATION OF WATER W County: JACKSON		<b>5</b> 1/4 1/4	Section Number	Township No. T 6 S	Range Number R /3 ■E □W	
Street/Rural Address of Well Location; if unknown, distance & direction			Global Positioning			
	ion: If at owner's address, checl				(in decimal degrees)	
2/2 WEST & 1/2 SOUTH OF CIRCLEVILLE			Longitude: (in decimal degrees)			
			Elevation:			
2 WATER WELL OWNER.	TEARY DAY		Datum: WGS 8	4, 🗌 NAD 83, 🗀	] NAD 27	
2 WATER WELL OWNER: JERRY RAY			Collection Method:			
RR#, Street Address, Box #: 23891 H RD. City, State, ZIP Code  PERMIT NO: 21230 HOLTON, KS 66436			☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
DECIMAL AND 71730	HOLTON, KS 664	136	Est. Accuracy:			
3 LOCATE WELL					, v . v	
WITH AN "X" IN 4 DEI	PTH OF COMPLETED WEL	L <b>Z.O.</b>	<b>ว</b> ft.			
SECTION BOX: Depth(						
N WELL	WELL'S STATIC WATER LEVEL/.2.4ft. below land surface measured on mo/day/yr. 1.9/16 1/2					
	Pump test data: Well water wasft. after hours pumping gpm					
EST. YIELD						
W   E   Bore Hole Diameter						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☑ Other (Specify below)						
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well ∠/UESTOCK						
Was a chemical/bacteriological sample submitted to Department? Yes No						
S If yes, mo/day/yr sample was submitted						
water went distincted: [1] Tes [1] To						
5 TYPE OF CASING USED: Steel Z PVC Other						
CASING JOINTS: Q Glued    Clamped    Welded    Threaded						
Casing diameter						
Casing neight above land surface in., Weight A.D						
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)						
Louvered shutter Key punched Wire wrapped X Saw cut Other (specify)						
SCREEN-PERFORATED INTERVALS: From. 13.9 ft. to 150 ft., From 1.70 ft. to 20.0 ft.						
From						
GRAVEL PACK INTERVALS: From						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other.						
Grout Intervals: From						
· — · —	_	Livestock	pens 🔲 Insecticide	storage	ner (specify below)	
		Fuel storag		_	ier (speerly delow)	
Watertight sewer lines Seepage pit Feedvard Fertilizer sto			torage	ns well		
Direction from well	INE PRESENT		from well			
	THOLOGIC LOG	FROM	TO LITHO. L	OG (cont.) <u>or</u> PLU	JGGING INTERVALS	
O 3 TOPSOIL						
3 39 YELLOW C	LAY					
39 121 GRAY CL	AY					
121 134 GAAY S	HALE					
	VALE (SOFT)					
142 176 GRAY SH	ALE					
	HAVE (SOFT)					
181 200 GAMY	SMALE					
7 CONTRACTORS OR LAND	OWNED'S CEDTIES ATIO	N. This was	or well was Promit	noted December	nated on Dalaria	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) O and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 51. 2. This Water Well Record was completed on (mo/day/year) 120/12.						
under the business name of BLOE VALLEY DALLING TWC. by (signature)						
INSTRUCTIONS: Use typewriter or ba					et answers. Send three copies	
(white, blue, pink) to Kansas Departmen	t of Health and Environment, Bureau	of Water, Geol	ogy Section, 1000 SW Ja	ckson St., Suite 420,	Topeka, Kansas 66612-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.						
KSA 82a-1212						
ILOI I OLG ILIL						