

KA

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

caa

1. Location of well:		County Jackson	Fraction NE 1/4 NE 1/4 SW	Section number 22	Township number T 6 S	Range number R 15 E
2. Distance and direction from nearest town or city: 4 N Street address of well location if in city: Holton			3. Owner of well: Gale Hagg R.R. or street: R.R. #1 City, state, zip code: Holton, Ks. 66436			
4. Locate with "X" in section below:		Sketch map:			6. Bore hole dia. 10 in. Completion date 6-9-78 Well depth 113 ft.	
					7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
5. Type and color of material		From	To	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
Top Soil		0	4	9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 24 in. RMP <input type="checkbox"/> PVC blue Weight 2.74 lbs./ft. Dia. 5 in. to 113 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 1258		
Brown Clay		4	43	10. Screen: Manufacturer's name Pumped Type PVC Dia. 5" Slope gauze 020 Length 40 Set between 73 ft. and 113 ft. <input type="checkbox"/> ft. and <input type="checkbox"/> ft.		
Blue Clay		43	88	Gravel pack? YES Size range of material 030/060		
Med. Chest Gravel		88	90	11. Static water level: <input type="checkbox"/> mo./day/yr. 70 ft. below land surface Date 6-9-78		
Blue Clay		90	108	12. Pumping level below land surfaces: Air Test <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 6 g.p.m.		
Blue Med. Sand		108	110	13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
Blue Clay		110	113	14. Well head completion: Top Cap <input type="checkbox"/> Pitless adapter 24 inches above grade		
				15. Well grouted? YES With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: * ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
				17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Jacuzzi Model number 5348 HP 1/2 Volts 230 Length of drop pipe 100 ft. capacity 10 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation: 1130 Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		19. Remarks: owner to install slab #16 well in milo field			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. STRADER Dale W 182 Business name License No. Address RT1 Holton, Ks Signed Dave Adams Date 6-29-78 Authorized representative	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

1-6
150
1-2
NE 1/4
1/4
1/4
1/4

< 1017