

1 LOCATION OF WATER WELL: County: JACKSON	Fraction SE 1/4 NE 1/4 SE 1/4	Section Number 16	Township Number T 6 S	Range Number R 15 EW
----------------------------------------------	----------------------------------	----------------------	--------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?

12719 ALDETH RD., HOLTON, KS

2 WATER WELL OWNER: ARMY CORPS OF ENGINEERS - KANSAS CITY DISTRICT	RR#, St. Address, Box # : 601 E 12TH ST City, State, ZIP Code : KANSAS CITY, MO 64105	Board of Agriculture, Division of Water Resources Application Number:
--------------------------------------------------------------------	------------------------------------------------------------------------------------------	--------------------------------------------------------------------------

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 24.7 ft. ELEVATION:
------------------------------------------------------	-----------------------------------------------------------------

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Domestic (lawn & garden)	<input checked="" type="radio"/> 10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<input checked="" type="radio"/> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 14.45 ft., Dia			Threaded
Casing height above land surface 2.47 in., weight			lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION MATERIAL:	<input checked="" type="radio"/> PVC	10 Asbestos-Cement	
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS
11 Other (Specify)			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<input checked="" type="radio"/> 3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 24.7 ft. to 14.45 ft.,	From ft. to ft.,	From ft. to ft.
GRAVEL PACK INTERVALS:	From 25 ft. to 11.45 ft.,	From ft. to ft.,	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<input checked="" type="radio"/> Bentonite	4 Other
Grout Intervals: From 10.45 ft. to SURFACE ft.,	From ft. to ft.,	From ft. to ft.,	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				14 Abandoned water well
				15 Oil well/Gas well
				<input checked="" type="radio"/> 16 Other (specify below)
				FORNER ATLAS F. MISSILE
				SILO (TCE)

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	BRN SILTY CLAY LOAM			
1	6	YLLW BRN CLAY W/FILL			
6	9	DK YLLW BRN SANDY CLAY			
9	19	YLLW BRN F-M SAND			
19	24	F-C SAND + GRAVEL			
24	25	DK GRY CLAY W/GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="radio"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11 / 16 / 04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 658 This Water Well Record was completed on (mo/day/yr) 01 / 25 / 05 under the business name of BOARD LONGYEAR by (signature) [Signature]
