


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: JACKSON SE 1/4 NE 1/4 SE 1/4 16 T 6 S R 15 EW

Distance and direction from nearest town or city street address of well if located within city?
 12719 Aldeth RD., HOLTON, KS

2 WATER WELL OWNER: ARMY CORPS OF ENGINEERS - KANSAS CITY DISTRICT
 RR#, St. Address, Box # : 601 E 12TH ST Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : KANSAS CITY, MO 64105 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL 82.22 ft. ELEVATION:

 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 2 in. to 71.97 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 2.85 in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 82.22 ft. to 71.97 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 85 ft. to 68.97 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 67.97 ft. to SURFACE ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 Direction from well? How many feet? FORMER ATLAS F. MISSILE SILO (TCE)

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	FILL			
3	4	DK BRN SILT LOAM/CLAY			
4	8	YLLW BRN SILTY CLAY			
8	12	DK GRY SILTY CLAY			
12	28	YLLW BRN SILTY CLAY			
28	29.5	YLLW BRN F-M SAND			
29.5	33	MED GRY SILTY CLAY			
33	37	YLLW BRN F-M SAND			
37	37.5	GRY BRN SILTY CLAY			
37.5	61.5	YLLW BRN F-M SAND			
61.5	65.5	GRY F-M SAND			
65.5	81	DK GRY F-M SAND			
81	85	DK GRY CLAY W/ GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11 / 29 / 04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 458 This Water Well Record was completed on (mo/day/yr) 01 / 25 / 05 under the business name of BOART LONGYEAR by (signature)