

46 WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 5 Township Number T 6 S Range Number R 17 E/W
 County: Atchison
 Distance and direction from nearest town or city street address of well if located within city?
1 3/4 Mi. W of Muscotah

2 WATER WELL OWNER: Laurence Meyers
 RR#, St. Address, Box #:
 City, State, ZIP Code: Muscotah, Kansas 66058
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N			
W	NW	NE	E
	SW	SE	
S			

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 6-21-77
 Depth(s) Groundwater Encountered 1. 32 ft. 2. 32 ft. 3. 32 ft.
 WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 6 ft. after 8 hours pumping 60 gpm
 Est. Yield 6 gpm: Well water was 20 ft. after 8 hours pumping 60 gpm
 Bore Hole Diameter 10 in. to 20 ft., and 8 in. to 60 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes ✓ No ✓

5 TYPE OF BLANK CASING USED:
 1 Steel ☒ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile ☐ CASING JOINTS: Glued ✓ Clamped ✓
 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) ☐ Welded ✓
 7 Fiberglass ☐ Threaded ✓
 Blank casing diameter 6 7/8 in. to 80 ft., Dia. 18 in. to 80 ft., Dia. 0.255 in. to 80 ft.
 Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 0.255
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☐ 8 RMP (SR) ☐ 10 Asbestos-cement ☐
 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 9 ABS ☐ 11 Other (specify) ☐
 12 None used (open hole) ☐
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot ☐ 3 Mill slot ☒ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole) ☐
 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes ☐
 7 Torch cut ☐ 10 Other (specify) ☐
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From 50 ft. to 80 ft.
 From 25 ft. to 80 ft., From 50 ft. to 80 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 80 ft., From 50 ft. to 80 ft.
 From 25 ft. to 80 ft., From 50 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement ☐ 2 Cement grout ☐ 3 Bentonite ☒ 4 Other ☐
 Grout Intervals: From 4 ft. to 20 ft., From 50 ft. to 80 ft., From 50 ft. to 80 ft.
 What is the nearest source of possible contamination:
 1 Septic tank ☐ 4 Lateral lines ☐ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well ☒
 2 Sewer lines ☐ 5 Cess pool ☐ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well ☐
 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below) ☐
 13 Insecticide storage ☐
 Direction from well? South How many feet? 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	7	Top Soil			
7	30	Yellow Clay			
30	32	Creek Bed Gravel			
32	80	Soft Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-21-77 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 317 This Water Well Record was completed on (mo/day/yr) 6-18-81
 under the business name of Williams Well Drilling by (signature) James Kramer
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.