


1 LOCATION OF WATER WELL: County: Atchison Fraction: SW 1/4 SE 1/4 SW 1/4 Section Number: 10 Township Number: T 6 S Range Number: R 17 EW

Distance and direction from nearest town or city street address of well if located within city?
From Muscotah .25 mi East 1 mi. South 1500' East + 350' N approx.

2 WATER WELL OWNER: Kelly Wood
 RR#, St. Address, Box #: 6624 Decatur Rd Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Effingham, KS 66023 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 7.7 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 49 ft. below land surface measured on mo/day/yr 7-25-06
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 2 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded
 Threaded
 Blank casing diameter: 5 in. to 5.7 in. Dia ft. Dia in. to ft. Dia in. to ft.
 Casing height above land surface: 36 in., weight: 2.87 lbs./ft. Wall thickness or gauge No. SDR 21
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 5.7 ft. to 7.7 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.5 ft. to 7.7 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage House New House to
 Direction from well? East (House) West (Livestock Pens) 1000' (Pens) How many feet? ± 100 be constructed

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	Brown Clay			
10	31	Brown Sandy Clay			
31	38	Grey Clay			
38	40	Brown Clay			
40	41	Brown Sandy Clay			
41	42	Brown Clay + 1/4" Brown Gravel			
42	43	Coarse Sand + Gravel 1/8" x 1/4"			
43	47	Brown-Grey Clay			
47	52	Brown Gravel 1/4" x 3/4" Chert			
52	57	Brown-Grey Clay			
57	59	Grey Clay - Brown Finesand - CS - 1/4" Gravel			
59	66.5	Grey Shale			
66.5	67	Grey Limestone			
67	81	Grey Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-24-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 739 This Water Well Record was completed on (mo/day/yr) 8-7-2006 under the business name of Rork Drilling by (signature) Mike Rork