

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

[Empty box for application number]


1 LOCATION OF WATER WELL: County: Atchison Fraction SW 1/4 SW 1/4 NW 1/4 Section Number 22 Township Number T 6 S Range Number R 17 EW

Distance and direction from nearest town or city street address of well if located within city? 1/4 mi. East, 2 1/2 mi. South + 66' East approx. of Muscotah

Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Mike Ptomey RR#, St. Address, Box #: 201 W. 1st St City, State, ZIP Code: Muscotah, KS 66058

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL 58.5 ft. Depth(s) Groundwater Encountered (1) 16 ft. below land surface measured on mo/day/yr 8-11-2007. Pump test data: Well water was 75 gpm. Est. Yield 75 gpm. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yrs Sample was submitted. Water well disinfected? Yes X No

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass. CASING JOINTS: Glued X Clamped Welded Threaded

Blank casing diameter 5 in. to 48.5 ft., Diameter. Casing height above land surface 22 in., Weight 2.87 lbs./ft. Wall thickness or gauge No. SDR 21

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 48.5 ft. to 58.5 ft., From. GRAVEL PACK INTERVALS: From 25 ft. to 58.5 ft., From

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other. Grout Intervals: From 2 ft. to 25 ft., From

What is the nearest source of possible contamination: Sewer system not installed at time of well const. 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well Existing Well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well. Direction from well? NE Septic Tank / SE Well. How many feet? Septic 73' / Well 32'

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows show depth intervals and lithology: 0-2 Topsoil, 2-5 Brown Clay, 5-25 Light Brown Clay, 25-38 Grey-Brown Clay, 38-42 Grey Clay, 42-48 Brown-Grey Silt, 48-52 Fine Brown Sand, 52-58 Medium Brown Sand, 58-60 Medium Grey Sand.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-11-2007 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 739. This Water Well Record was completed on (mo/day/year) 8-24-2007 under the business name of Rock Drilling by (signature) Mike Rock

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.