			WATER	WELL REC	ORD I	-orm wwc-	5 KSA 8	2a-1212				
LOCATION OF WATER WELL:			Fraction	CTP	CM	- 1	ction Numb		hip Number	1	Number	
County: ATCHISON Distance and direction from nearest town of			SE 1/4		4 SW	1/4	4	Т	6 s	R	18 E/	w
Distance and	direction		-									
<del>                                     </del>		-	rth, 1/2 we		ffingn	<u>am</u>						
WATER V	WELL OW		son Solid V									
RR#, St. Add	dress, Box		im Goodman		house	EF	FINGHAM	SITE Boar	d of Agriculture,	Division of W	ater Resc	urces
City, State, Z			son, KS 66				¥		cation Number:			
LOCATE V	WELL'S LO	DCATION WITH 4 BOX:	DEPTH OF CO Depth(s) Groundw									
<u>,                                     </u>	1		VELL'S STATIC V									
1	- i -	i     '							hours pu			
J	NW	NE	st. Yield . 1./.2 .									
<u>'</u>	_!		Sore Hole Diamet									
* w												п.
<u> </u>	-i I	\\	VELL WATER TO			5 Public wat			-	Injection well		
1	SW	SE	1 Domestic	3 Feed		Oil field wa			g 12			
	_1 <b> </b>	·	2 Irrigation	4 Indus				411	g well			
	1 X		Vas a chemical/ba	acteriological	sample si	ubmitted to E			_	,	•	s sub-
	\$		nitted						nfected? Yes 2			
引 TYPE OF	BLANK C	ASING USED:		5 Wrought in	ron	8 Conc			G JOINTS: Glue	dXCla	mped	
1 Steel		3 RMP (SR)		6 Asbestos-	Cement	9 Other	(specify be	low)	Weld	ed		
2 PVC		4 ABS		7 Fiberglass						aded		
		4." ir										
Casing heigh	it above la	ind surface2	2.4 " i	n., weight	2.04		lb	s./ft. Wall thick	ness or gauge N	o <b>.</b> 327	1	
TYPE OF SC	CREEN OF	R PERFORATION	MATERIAL:			7 P	/C	10	Asbestos-ceme	ent		
1 Steel		3 Stainless	steel	5 Fiberglass	;	8 RI	MP (SR)	1	Other (specify)			
2 Brass	s	4 Galvanized	d steel	6 Concrete t	tile	9 A	38	13	None used (op	en hole)		
SCREEN OF	PERFOR	RATION OPENING	S ARE:		5 Gauze	d wrapped		8 Saw cut		11 None (o	pen hole	)
1 Conti	inuous slo	t 3 Mill	slot		6 Wire w	vrapped		9 Drilled h	oles	·		
2 Louve	ered shutt	er 4 Kev	punched		7 Torch	• •			pecify)			
		D INTERVALS:		12			ft F		ft. t			
									ft. t			
GB	AVEL PAG	CK INTERVALS:							ft. t			
۵.,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			52	ft. to	55	ft., F		ft. 1			ft.
GROUT N	ΛΑΤΕΡΙΔΙ	: 1 Neat ce		Cement gro		3 Bent						
Grout Interva		nft										
		urce of possible of		11., 1101		O		estock pens		bandoned wa		
_		•		7 04	meis n.			•		Dil well/Gas w		
•	1 Septic tank 4 Lateral lii						11 Fuel st					
2 Sewe		5 Cess p				on		rtilizer storage	т д С	ill trer	below)	
	_	er lines 6 Seepaq north	ge pit	9 Fee	edyard			ecticide storage	30'	++.+ ++ 9.	<del>, , , , , , , , , , , , , , , , , , , </del>	
Direction from		HOLCH	LITUOLOGICA		_	1 50014		nany feet?		NTERVALO		
FROM	TO		LITHOLOGIC L	OG		FROM	ТО		PLUGGING I	NIERVALS		
0	16	Clay-Brown					<del></del>					
16	43	Clay-Grey								4		
43	47		-Coarse Sar	ia-Dirty	-Clay-	Hrown		<del> </del>				
47	53	Clay-Grey				+						
53	54		-Coarse SAr	nd-Med-G	ravel			ļ				
		Clay-Brown	<b>1</b>									
54	60	Clay-Brown	n							,		
							<b>T</b>					
J	070-:-								(0)	1		
		R LANDOWNER'S										
•		year) 6-							-			ınsas
Water Well C	Contractor's	s License No				ell Record w	•	. / . !	r) 1.7.2	9 9.	·	
under the bu	siness nar	ne of STRADE	ER DRILLING	CO., II	NC.		by (sig	nature)	allles	eren		
		pewriter or ball point peent, Bureau of Water, To									s Departmen	nt