

1 LOCATION OF WATER WELL: Fraction $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$ Section Number 20 Township Number T 6 S Range Number R 20 **EW**
 County: **Atchison**

Distance and direction from nearest town or city street address of well if located within city?
4 miles southwest of Atchison, KS

2 WATER WELL OWNER: **ContiGroup Companies**
 RR#, St. Address, Box # : **U.S. Highway 59 West**
 City, State, ZIP Code : **Atchison, KS 66002**
 Board of Agriculture, Division of Water Resource:
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX

N			
-NW-		-NE-	
W		X	E
-SW-		-SE-	
S			

4 DEPTH OF COMPLETED WELL 28' ft. ELEVATION: 1059.42
 Depth(s) Groundwater Encountered 1 26.1-27' ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 24.4 ft. below land surface measured on mo/day/yr 8/11/06
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield UNK gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded
 Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 2.4 in., weight lbs./ft. Wall thickness or gauge No. sch 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 0.01 slot ft.
 7 Torch cut
 SCREEN-PERFORATED INTERVALS: From 18 ft. to 28 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 16 ft. to 28 ft., From ft. to ft.
Bentonite From 28 ft. to 16 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 11.16 ft., From ft. to ft., From 28 ft. to 32 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.9	Brown silty clay fill			
3.9	7.0	Black topsoil			
7.0	17.0	Brown silty clay			
17	20.3	Grey and brown silty clay			
20.3	26.1	Grey and brown silty clay			
26.1	27	Brown clayey sand, wet			
27	32	Grey silty clay			

RECEIVED
MAY 1 2007
BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/5/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 597 This Water Well Record was completed on (mo/day/yr) MAY 27, 2007 under the business name of ProSonic Corp. by (signature) [Signature]