LOCATION OF WATER WELL:   Fraction   NE   NW   NE   O1	ft. 3 d on mo/da urs pumpir urs pumpir urs pumpir 12 Other l) No X; If ted? Yes S: Glued Welded Threade in. to	R 20 (1) ees, min. of 4 digit file file file file file file file file
Distance and direction from nearest town or city street address of well if cloated within city?  1400 Skyway Drive, Atchison. KS  2 WATER WELL OWNER: Wood Oil Co. – Mike Wood RR#, St. Address, Box # : PO BOX 67 City. State. ZIP Code : Leavenworth. KS 66048  3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: N  WELL'S STATIC WATER LEVEL N  Depth(s) Groundwater Encountered 1  Pump test data: Well water was ft. after ho WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well)  Was a chemical/bacteriological sample submitted to Department? Yes Sample was submitted  Water Well Disinfect  TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT's 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  (2 PVC) 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight  TYPE OF SCREEN OR PERFOR ATION MATERIAL:	ft. 3 d on mo/da urs pumpir urs pumpir ng 11 Inj 12 Other l) No X; If ted? Yes S: Glued Welded Threade in. to	fing gpm  ection well r (Specify below  yes, mo/day/yrs No X  Clamped
1400 Skyway Drive, Atchison. KS  2 WATER WELL OWNER: Wood Oil Co. – Mike Wood RR#, St. Address, Box # : PO BOX 67 City, State, ZIP Code : Leavenworth, KS 66048  3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: N  WELL'S STATIC WATER LEVEL N  Pump test data: Well water was N  WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well)  Was a chemical/bacteriological sample submitted to Department? Yes Sample was submitted Water Well Disinfect TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight  TYPE OF SCREEN OR PERFORATION MATERIAL:	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
RR#, St. Address, Box # : PO BOX 67 City, State, ZIP Code : Leavenworth, KS 66048  Data Collection Method:  LOCATE WELL'S   4 DEPTH OF COMPLETED WELL   23' ft.    LOCATON WITH AN "X" IN SECTION BOX:  N Depth(s) Groundwater Encountered 1	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
RR#, St. Address, Box # : PO BOX 67 City, State, ZIP Code : Leavenworth, KS 66048  Data Collection Method:  LOCATE WELL'S   4 DEPTH OF COMPLETED WELL   23' ft.    LOCATON WITH AN "X" IN SECTION BOX:  N Depth(s) Groundwater Encountered 1	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
City, State, ZIP Code : Leavenworth, KS 66048   Data Collection Method:  3 LOCATE WELL'S   4 DEPTH OF COMPLETED WELL   23' ft.    LOCATON   WITH AN "X" IN   SECTION BOX:   Depth(s) Groundwater Encountered 1   -15' ft. 2    WELL'S STATIC WATER LEVEL   3 ft. after   ho    Est. Yield   gpm: Well water was   ft. after   ho    WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditionin 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes   1    Sample was submitted   Water Well Disinfec   Water Well Disinfec   Water Well Disinfec   TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS    1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)    (2 PVC) 4 ABS 7 Fiberglass   Tiberglass   In. to   ft., Dia    Casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in., Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in. Weight   Ibs./ft. Wall thickness of the concrete in the casing height below land surface   4.56   in. Weight   Ibs./ft. Wall thickness of the concrete in the concrete in the concrete in the casing height below land surface   4.56   in. Weight   Ibs./ft. Wall thi	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
LOCATON WITH AN "X" IN SECTION BOX:  WELL'S STATIC WATER LEVEL  Pump test data: Well water was ft. after ho Est. Yield gpm: Well water was ft. after ho WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes  TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  (2 PVC) 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete in the concentration of the concentration in the casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concentration of the concentration in the case of the concentration of the concentration of the case of the ca	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
WITH AN "X" IN SECTION BOX:  WELL'S STATIC WATER LEVEL  Pump test data: Well water was ft. after how well water supply 8 Air conditioning 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes Sample was submitted water was ft. after how well was a chemical/bacteriological sample water supply 9 Dewatering well was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted water was ft. after how well was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted water was ft. after how well water supply 9 Dewatering well was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted water was ft. after how well water was ft. after how water was ft. after how well water was ft. after how well water was ft. after how well water was ft. after how water wa	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
Pump test data: Well water was it. after how was pump. Well water was ft. after how well water was ft. after how well water was ft. after how well water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted water well Disinfect Water Well Disinfect 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the steel of the ste	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
Pump test data: Well water was ft. after how was pump. Well water was ft. after how well water was ft. after how well water was ft. after how well water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted water well Disinfect Water Well Disinfect 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the steel of the surface was ft. after how water was ft. after how well water was ft. after how water was ft. a	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpr ng gpr ection well r (Specify below Fyes, mo/day/yrs No X Clamped
Pump test data: Well water was ft. after how was pump. Well water was ft. after how was pump. Well water was ft. after how was pump. Well water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted water well Disinfect 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the steel in the case of the case	urs pumpir urs pumpir ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ng gpri ng gpri ng gpri ection well r (Specify below Fyes, mo/day/yrs No X Clamped
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well 3 Sample was submitted Water Well Disinfect 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass 3 Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the source of th	ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ection well r (Specify below  yes, mo/day/yrs No X  Clamped
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) (10 Monitoring well 3 Sample was submitted Water Well Disinfect TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass Stank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the control of the control of the control of the casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the control of the	ng 11 Inj 12 Other I) No X; If ted? Yes S: Glued Welded Threade in. to	ection well r (Specify below  yes, mo/day/yrs No X  Clamped
Was a chemical/bacteriological sample submitted to Department? Yes  Sample was submitted  Water Well Disinfect  TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  (2 PVC) 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia  Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:  Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:	No X; If ted? Yes S: Glued Welded Threade in. to	yes, mo/day/yrs No X Clamped
Was a chemical/bacteriological sample submitted to Department? Yes  Sample was submitted  Water Well Disinfect  TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  (2 PVC) 4 ABS 7 Fiberglass  Clank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia  Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:  Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:  Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:	No X; If ted? Yes S: Glued Welded Threade in. to	yes, mo/day/yrs No X Clamped
Was a chemical/bacteriological sample submitted to Department? Yes 1 Sample was submitted Water Well Disinfect TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass Slank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINTS (2 PVC) 4 ABS 7 Fiberglass Slank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia Casing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINTS (2 PVC) 4 ABS 7 Fiberglass (3 PVC) 4 ABS 7 Fiberglass (4 PVC) 4 ABS 7 Fiberglass (5 PVC) 4 ABS 7 Fiberglass (6 PVC) 4 ABS 7 Fiberglass (7 PVC) 4 ABS 7 Fiberglass (8 PVC) 4 ABS 7 Fiberglass (9 PVC) 4 ABS 7 Fiberglass (1 PVC) 4 ABS 7 Fiberglass (2 PVC) 4 ABS 7 Fiberglass (3 PVC) 4 ABS 7 Fiberglass (4 PVC) 4 ABS 7 Fiberglass (4 PVC) 4 ABS 7 Fiberglass (5 PVC) 4 ABS 7 Fiberglass (6 PVC) 4 ABS 7 Fiberglass (7 PVC) 4 ABS 7 Fiberglass (8 PVC) 4 ABS 7 Fiberglass (9 PVC) 4 ABS 7 Fiberglass (1 PVC) 4 ABS	s: Glued Welded Threade in. to	No X Clamped
S Sample was submitted Water Well Disinfect TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass clank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia classing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:  2 PVC) 4 ABS 7 Fiberglass Clark casing diameter 2 in. to 13 ft., Dia in. to ft., Dia classing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:	s: Glued Welded Threade in. to	No X Clamped
TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINT:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  (2 PVC) 4 ABS 7 Fiberglass  clank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia  classing height below land surface 4.56 in., Weight Ibs./ft. Wall thickness of the concrete tile CASING JOINT:  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)  7 Fiberglass  1 In. to ft., Dia  2 In. to ft., Dia  2 In. to ft., Dia  3 In. to ft., Dia  4 Ibs./ft. Wall thickness of the concrete tile CASING JOINT:	S: Glued Welded Threade in. to	Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass lank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia asing height below land surface 4.56 in., Weight lbs./ft. Wall thickness of	Welded Threade in. to	
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) (2 PVC) 4 ABS 7 Fiberglass lank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia asing height below land surface 4.56 in., Weight lbs./ft. Wall thickness of	Welded Threade in. to	
(2 PVC) 4 ABS 7 Fiberglass  clank casing diameter 2 in. to 13 ft., Dia in. to ft., Dia  classing height below land surface 4.56 in., Weight lbs./ft. Wall thickness of the company of the	Threade in. to	d X
VPF OF SCREEN OR PERFORATION MATERIAL.	in. to	
VPF OF SCREEN OR PERFORATION MATERIAL.	or gauge No	o ft.
YPE OF SCREEN OR PERFORATION MATERIAL:		o. Sch. 40 PVC
1 Steel 3 Stainless steel 3 Fiberglass (7 PVC) 9 ABS 11 Other (		
	specify)	
CREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot (3 Mill slot) 5 Guaze wrapped 7 Torch cut 9 Drilled holes 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)  CREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft. From  From ft to ft. From  GRAVEL PACK INTERVALS: From 11 ft. to 23 ft. From  From ft to ft. From	11 None (d	open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)		•
CREEN-PERFORATED INTERVALS: From 13 ft. to 23 ft. From	ft. to .	ft.
From ft. to ft. From	ft. to	ft.
GRAVEL PACK INTERVALS: From 11 ft. to 23 ft. From	ft. to .	ft.
Trom	**. 10 .	
GROUT MATERIAL: 1 Neat cement 2 Cement grout (3 Bentonite) 4 Other rout Intervals From 1 ft. to 11 ft. From ft. to ft. From		
rout Intervals From 1 ft. to 11 ft. From ft. to ft. From	ft	. to ft.
hat is the nearest source of possible contamination:		
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Stora		6 Other (specify
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water		below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well irection from well? How many feet?		Lust Site
	NG INTER	VALS
0 0.5 Asphalt 0.5 5   Clay. silty		
5 23 Clay		
	MW 5	
CODD	ECT	<b>=</b> D
- CURN		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2)	reconstruct	ed. or (3) plugged
der my jurisdiction and was completed on (mo/day/year)01/09/2008 and this record is true to the bes	t of my know	wledge and belief.
nsas Water Well Contractor's License No This Water Well Record was completed on me/day/ye	ear) <u>02/20/</u>	2008
der the business name of Coranco Great Plains, Inc. by (signature)		·
STRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and En blogy Section, 1000 SW Jackson St., Suite 420, Topelta, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER W	vironment, Bu	reau of water,
or records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.	LLL OWNER	and retain one for