

1 LOCATION OF WATER WELL: County: GRAHAM	Fraction NW 1/4 SW 1/4 SE 1/4	Section Number 6	Township Number T 6 S	Range Number R 22 E/W
--	---	----------------------------	---------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

13 MILES NORTH AND 2 MILES EAST OF HILL CITY KS

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	ALLEN TREXLER 2753 Q TERR HILL CITY KS 67642	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 1.05 ft. ELEVATION:
--	--

Depth(s) Groundwater Encountered 1 **8.5** ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL **8.5** ft. below land surface measured on mo/day/yr **1.0-2.9-0.4**

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield **2.0** gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
~~X~~ Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No **XX**; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No **XX**

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
X PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 8.5 ft., Dia in. to ft., Dia in. to ft.			Threaded
Casing height above land surface 18 in., weight 1.60 lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		XX PVC	10 Asbestos-Cement
1 Steel	3 Stainless Steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized Steel	6 Concrete tile	9 ABS
			11 Other (Specify)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	X Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS: From 8.5 ft. to 1.05 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 4.0 ft. to 1.05 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	X Bentonite	4 Other
Grout Intervals: From 0 ft. to 3.0 ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well?				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	10	SURFACE CLAY			
10	30	YELLOW CLAY & FINE SAND			
30	70	FINE SAND			
70	80	MED FINE SAND			
80	100	MED SAND SAND			
100	105	BLUE SHALE			
					RECEIVED
					DEC 02 2004
					BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was KIX constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1.0-2.9-0.4 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 4.4.4 This Water Well Record was completed on (mo/day/yr) 1.0-2.9-0.4 under the business name of ANDY ANDERSON DRILLING by (signature) <i>Andy Anderson</i>
