

USE TYPEWRITER OR BALL POINT PEN—PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment—Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County: CLAY CLAY	Fraction: SE 1/4 SE 1/4 SE 1/4	Section number: 32	Township number: T 4 S	Range number: R 34 EW
2. Distance and direction from nearest town or city: 3 1/2 N Street address of well location if in city: GREEN			3. Owner of well: ARMOND CHARBONNEAU R.R. or street: RT #1 City, state, zip code: GREEN, KANS 67447			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 9/30/74 Well depth 60 ft.		
				7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
TOPSOIL		0	2	9. Casing: Material PVC Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP PVC <input checked="" type="checkbox"/> Weight 3 lbs./ft. Dia. 5 in. to 60 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 1214		
BROWN CLAY		2	11	10. Screen: Manufacturer's name PUMPCO Type PVC Dia. 5" Slot/gauze 1/4" Length 30' Set between 40 ft. and 60 ft. ft. and ft. Gravel pack? YES Size range of material 8x4		
BROWN CLAY W/LIMESTONE		11	18	11. Static water level: no./day/yr. 40 ft. below land surface Date 9/30/74		
BROWN CLAY		18	24	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 8.5 g.p.m.		
RED CLAY		24	32	13. Water sample submitted: mo./day/yr. Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Date		
GRAY CLAY		32	36	14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade		
LIMESTONE		36	39	15. Well grouted? YES With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
GRAY CLAY		39	44	16. Nearest source of possible contamination: SEPTIC ft. Direction NW Type TANK Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
LIMESTONE		44	58	17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
BLUE SHALE		58	60			
STOP		60				
(Use a second sheet if needed)						
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. GEO COX + SONS INC 2-58 Business name License No. Address CLIFTON, KANS Signed Duane Cox Date 9/30/74 Authorized representative		

40-40-32-SESESE
1/4 1/4 1/4